

NO. OF COPIES RECEIVED	2
DISTRIBUTION	
SANTA FE	2
FILE	2
U.S.D.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10

Section Type of Lease
State For
5. Other No. 7. Lease No.
E 5232

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG OIL OR GAS RESERVOIR.
USE APPLICATION FOR PERMIT TO DRILL (FORM C-101) FOR ADDITIONAL DETAILS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	7. Unit Agreement Name BIG EDDY UNIT
2. Name of Operator PERRY R. BASS	8. Form of Lease Name BIG EDDY UNIT
3. Address of Operator Box 2760, MIDLAND, TX 79702-2760	9. Well No. 93
4. Location of Well UNIT LETTER K 1980 FEET FROM THE SOUTH LINE AND 1980 FEET FROM THE WEST LINE, SECTION 36 TOWNSHIP 21S RANGE 28E NMPM.	10. Field and Pool, or Wildcat INDIAN FLATS MOCCO
15. Elevation (Show whether DE, RT, GL, etc.) 3196.2' GL	12. County EDDY

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK
TEMPORARILY ABANDON
PULL OR ALTER CASING
OTHER

PLUG AND ABANDON
CHANGE PLANS

SUBSEQUENT REPORT OF:

REMEDIATION WORK
CONFIDENCE DRILLING OPNS.
CASING TEST AND CEMENT JOB
OTHER SPUD DATE, SURFACE CAS, 8 5/8" CSG.

ALTERING CASING
PLUG AND ABANDONMENT

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

SPUD 11:15 AM 1ST 3-7-82
DRLG. 15" HOLE TO 398'. RAN 9 JTS. 11 3/4" 42# H-40 STC CSG.
CEMENTED W/ 350 SYX. CLASS "C" CEMENT W/ ADDITIVES, DID NOT CIRC.
DUMPED PLUG, FLOAT HELD. DUMPED 200 SYX. CLASS "C" NEAT CEMENT
DOWN ANNULUS NO RETURNS. TAPPED OUT CEMENT W/ 5 YDS READY MIX.
WOC 20 HRS. TEST CSG @ BOP TO 1000 PSI HOLD OK, DRLG CEMENT, FLOAT,
& GUIDE STEEL DRLG 11" HOLE.
DRLG 11" HOLE TO 3450' 3-14-82
RAN 10 JTS. 8 5/8" 32# S-80 STC CSG. 69 JTS. 28# S-80 STC CSG. SET @ 3450'
CEMENTED W/ 1500 SYX. LITE "C" CEMENT W/ ADDITIVES TAPPED W/ 250 SYX. CLASS "C"
W/ ADDITIVES DISPLACED W/ 212 BOLS FRESH WTR. ANNULUS PLUG TO 1800 PSI @ 8:00 PM
CST 3-14-82. FLOAT HELD. CIRC 310 SYX. CEMENT. WOC 24 HRS.
DRLG. FLOAT, CEMENT & SHOES TESTED BOP TO 2000 PSI, TEST CSG. SEAT. TO
550 PSI ALL HELD OK. DRLD. 7 7/8" HOLE 3-15-82.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED J. J. Hurty, Jr. TITLE SP. PRODUCTION CLERK DATE 3-16-82
APPROVED BY M. W. Walker TITLE OIL AND GAS INSPECTOR DATE APR 16 1982
CONDITIONS OF APPROVAL, IF ANY: