

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator TXO Production Corp		Lease Cateau Draw St Com		Well # 2	
Location of Well	Unit 2000 FNL 890 FEL H	Section 18	Township 21	Range 26	County Eddy
Drilling Contractor	Warton Drllg Co		Type of Equipment Rotary		

* Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17 1/2	13 3/8"	48#		500'	200 SX Circ
12 1/4	8 5/8"	24#		2200'	800 SX Circ
7 7/8	4 1/2	11.6#		10,800'	1100 SX

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____
(Approved) (Rejected)

Inspected by _____ date _____

Cementing Program

Size of hole 12" Size of Casing 8 5/8" Sacks cement required 1800 Sxs.

Type of Shoe used guide Float collar used inst. Btm 3 jts welded yes

TD of hole 2250 Set 2253 Feet of 8 5/8 Inch 24 # Grade K-55

(New) used csg. @ 2250 with 200 sacks neat cement around shoe C.I.C. 2%

+ 200 sax Thixset 10# Gilsonite additives 1/4# / sk flocc + 250 H/L 10# Gilsonite 1/4# floc *

Plug down @ 7:30 (AM) (PM) Date 2/7/82

Cement circulated yes No. of Sacks 300 Sxs.

Cemented by Halliburton Witnessed by Harry Brooks

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: * 200 Thixset 10# Gilsonite 1/4# flocc, 250 Sxs. H/L 10# Gilsonite 1/4# flocc *