NM OIL CONS. COMMISSION		
Form 9-331 Drawe D Dec. 1973 Artesia, NM 88210	Form Approved. Budget Bureau No. 42–R1424	
UNITED STATES	5. LEASE	
DEPARTMENT OF THE INTERIOR	NM-34650	
C/SF GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME RECEIVED	
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME MAR 1 1 1982 Federal 30 Com	
1. oil gas 🕅 well 🕅 well		
2. NAME OF OPERATOR PH 915-684-7827	9. WELL NO. O. C. D.	
Glenn Cope 915-684-5247 RES	ARTESIA, OFFICE	
3. ADDRESS OF OPERATOR	Undesignated The task	
1604 W. Front Avenue, Midland, TX 79701	11. SEC., T., R., M., OR BLK. AND SURVEY OR	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	AREA 30-22S-25E	
AT SURFACE: 1090' FNL & 560 FEL of Sec 30-22S-	12. COUNTY OR PARISH 13. STATE	
AT TOP PROD. INTERVAL: 25E AT TOTAL DEPTH:	Eddy NM	
	14. API NO.	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,		
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF	B752 G.L.	
TEST WATER SHUT-OFF Image: Construction of the second	(NOTE: Report results of multiple completion or zone change on Form 9–330.) SURVEY EXICO	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2-20-82 - Ran 9 joints of 13 3/8" Surface Casing to 334'. Could not circulate casing past that depth. Cemented with 365 sacks of cement. Cemented down 1" with a total of 725 sacks in 28 jobs before cement circulated to surface. 2-27-82 - Drilled to 1900'. R.U. & ran 37 joints 9 5/8" 40# N-80 LT&C casing to 1484' and casing became lodged at that depth. Cemented 9 5/8" intermediate Csg @ 1484' with 450 sacks HOWCO LITE followed with 200 sacks Class C Neat Cement. Cement circulated .

*Note - Received virbal approval from Mr. Gilliam to set intermediate at that depth.

Subsurface Safety Valve: Manu. and T	ype	Set @ Ft.
18. I hereby certify that the foregoing SIGNED <u>Element Cepu</u>		ate <u>3-3-82</u>
APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	(This space for Federal or State office use)	ACCEPTED FOR RECORD
		LIAR 1 0 1982
	*See Instructions on Reverse Side	U.S. GEOLOGICAL SURVE