

Pennzoil "Winchester-Fed" No. 1
 1980' FNL & 660' FWL, Section 4,
 T-20-S, R-28-E, Eddy Co., NM
 GL 3296' KB 3312' TD 11,400'
 PBTD 11,350'

Comp Wlfc 7/82 Perfs 8849-9029'
 4-1/2" @ 11,390' w/1175 sxs class H

Estimated top of cement: ~~6300~~ 7200'

Proposed Cement: 6800'-5000' +/-

Proposed Perfs: ~~6448-6302~~ 6146, 6160,
 6181, 6195, 6199, 6214, 6224, 6242,
 6258, 6272, 6286, 6300'.

Schlumberger		SIMULTANEOUS COMPENSATED NEUTRON- FORMATION DENSITY																																																																																																																									
COMPANY <u>PENNZOIL COMPANY</u> WELL <u>WINCHESTER FEDERAL NO. 1</u> FIELD <u>WINCHESTER</u> COUNTY <u>EDDY</u> STATE <u>NEW MEXICO</u>																																																																																																																											
1980' FNL & 660' FEL SERIAL NO. <u>4</u> REC <u>20-S</u> INDEX <u>28-E</u>		Other Services <u>DLL/MSFL</u> <u>38</u>																																																																																																																									
Permanent Datum: <u>G.L.</u> Elev. <u>3296.4</u> Log Measured From: <u>K.B.</u> <u>13.8</u> Ft. Above Perm. Datum Drilling Measured From: <u>K.B.</u>		Elev. <u>K.B. 3312.1</u> D.F. <u>01.3236.5</u>																																																																																																																									
<table border="1"> <tr> <td>Date</td> <td>6-21-82</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Run No.</td> <td>ONE</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Depth - Emitter</td> <td>11300</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Depth - Logger</td> <td>11397</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Dist. Log Interval</td> <td>11394</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Top Log Interval</td> <td>SURFACE</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Coring - Driller</td> <td>8 5/8 2595</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Coring - Logger</td> <td>2595</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Bit Size</td> <td>7 7/8</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Type Fluid In Hole</td> <td>SALT GEL/PO. YHER</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Dens. Visc.</td> <td>10.1 36</td> <td></td> <td></td> <td></td> </tr> <tr> <td>pH Fluid Loss</td> <td>9.0 4.2 ml</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Source of Sample</td> <td>HUOCL</td> <td></td> <td></td> <td></td> </tr> <tr> <td>No. @ Meas. Temp.</td> <td>1.057 @ 86 °F</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Half @ Meas. Temp.</td> <td>1.058 @ 83 °F</td> <td></td> <td></td> <td></td> </tr> <tr> <td>One @ Meas. Temp.</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Source, Rod & Line</td> <td>MEAS. 1.025 @ 122 °F</td> <td></td> <td></td> <td></td> </tr> <tr> <td>No. @ Bit</td> <td>2330 6-20</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Circulation Stopped</td> <td>0555 6-21</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Logger on Bottom</td> <td>172</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Max. Rec. Temp.</td> <td>0185 RSML</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Equip. Location</td> <td>FREDMAN</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Recorded by</td> <td>HAIR</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Witnessed by</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>				Date	6-21-82				Run No.	ONE				Depth - Emitter	11300				Depth - Logger	11397				Dist. Log Interval	11394				Top Log Interval	SURFACE				Coring - Driller	8 5/8 2595				Coring - Logger	2595				Bit Size	7 7/8				Type Fluid In Hole	SALT GEL/PO. YHER				Dens. Visc.	10.1 36				pH Fluid Loss	9.0 4.2 ml				Source of Sample	HUOCL				No. @ Meas. Temp.	1.057 @ 86 °F				Half @ Meas. Temp.	1.058 @ 83 °F				One @ Meas. Temp.					Source, Rod & Line	MEAS. 1.025 @ 122 °F				No. @ Bit	2330 6-20				Circulation Stopped	0555 6-21				Logger on Bottom	172				Max. Rec. Temp.	0185 RSML				Equip. Location	FREDMAN				Recorded by	HAIR				Witnessed by				
Date	6-21-82																																																																																																																										
Run No.	ONE																																																																																																																										
Depth - Emitter	11300																																																																																																																										
Depth - Logger	11397																																																																																																																										
Dist. Log Interval	11394																																																																																																																										
Top Log Interval	SURFACE																																																																																																																										
Coring - Driller	8 5/8 2595																																																																																																																										
Coring - Logger	2595																																																																																																																										
Bit Size	7 7/8																																																																																																																										
Type Fluid In Hole	SALT GEL/PO. YHER																																																																																																																										
Dens. Visc.	10.1 36																																																																																																																										
pH Fluid Loss	9.0 4.2 ml																																																																																																																										
Source of Sample	HUOCL																																																																																																																										
No. @ Meas. Temp.	1.057 @ 86 °F																																																																																																																										
Half @ Meas. Temp.	1.058 @ 83 °F																																																																																																																										
One @ Meas. Temp.																																																																																																																											
Source, Rod & Line	MEAS. 1.025 @ 122 °F																																																																																																																										
No. @ Bit	2330 6-20																																																																																																																										
Circulation Stopped	0555 6-21																																																																																																																										
Logger on Bottom	172																																																																																																																										
Max. Rec. Temp.	0185 RSML																																																																																																																										
Equip. Location	FREDMAN																																																																																																																										
Recorded by	HAIR																																																																																																																										
Witnessed by																																																																																																																											

DEC 29 '80
 NOV 20 '80

SEP 0 1

NOV 20 '80

FEB 2 1981

FEB 2 6 1981

