

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Artesia, NM 88210

LEASE

NM 15882

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

OCT 7 1982

2. NAME OF OPERATOR

Yates Petroleum Corporation

O. C. D.

3. ADDRESS OF OPERATOR

207 South 4th St., Artesia, NM 88210

ARTESIA, OFFICE

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660 FNL & 660 FWL, Sec. 11-20S-29E

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Burton Federal

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Wildcat 7 River

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unit D, Sec. 11-T20S-R29E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3308' GR

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) ☐

☒

☐

☐

☐

☐

☐

☐

☐

☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED
OCT 11 1982

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded a 12" hole with Cable tool rig at 3:00 PM 6-30-82. Ran 10-3/4" casing to 140'. Ran 8-5/8" 24# casing and pulled 10-3/4" casing. Ran 8-5/8" casing to 230'. Ran 7" 20# casing and pulled 8-5/8" casing. Set 7" 20# casing at 480'. Cemented w/200 sacks Lite and 100 sacks Class "C" 3% CaCl₂. PD 1:00 PM 7-28-82. Cement did not circulate. WOC 8 hours. Ran Temperature Survey and found top of cement at 90'. Ran 1". Tagged cement at 95'. Spotted 75 sacks Class "C" 2% CaCl₂. PD 7:45 AM 7-29-82. Bumped plug to 500 psi, released pressure and float held okay. Cement circulated 25 sacks. WOC. Drilled out 7:00 PM 7-29-82. WOC 18 hrs. Rig down for repairs for 4 days.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] ACCEPTED FOR RECORD TITLE Engineering Secty DATE 8-10-82

(This space for Federal or State office use)

APPROVED BY [Signature] DATE OCT 5 1982

TITLE _____ DATE _____

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side