

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☐ well other Drilling

2. NAME OF OPERATOR

Liberty Oil & Gas

3. ADDRESS OF OPERATOR Suite 200 77380

1776 Woodstead Ct. The Woodlands, Tx.

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FSL & 1980' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Casing and Cement ☒

5. LEASE

NM-15873

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Doris Federal

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Burton Flat-Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 26, T20S, R28E

12. COUNTY OR PARISH

Eddy


13. STATE

N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3263.5' GR



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8/5/83 Intermediate casing point 2900'.

Ran 72 jts(2900'), 9 5/8", 36.0#, J-55, ST&C casing and set @ 2900'. Set DV tool and cement basket @ 1488'. Cement 1st stage with 475 sx Class 'C' 65-35 poz-mix followed by 200 sx Class 'C'. P.O.B. 1st stage @ 11:30 P.M. 8/5/83. W.O.C. 12 hours.

Cement 2nd stage with 450 sx Class 'C' followed by 200 sx Class 'C', 2% CaCl. P.O.B. 7:00 A.M. 8/6/83. Circulated 125 sx of cement to surface. W.O.C. 12 hours. Pressure tested casing 1500 psi for 30 minutes.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Levy L. Franklin

TITLE

Agent

DATE

10/7/83

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

OCT 11 1983

*See Instructions on Reverse Side

ROSWELL, NEW MEXICO