

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

Perry R. Bass

3. ADDRESS OF OPERATOR

P. O. Box 2760 Midland, Texas 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY See space 17 below.)

AT SURFACE: 660' FNL 1980' FEL Unit Letter B

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) 4-1/2" Liner

SUBSEQUENT REPORT OF:

MINERAL CONSERVATION COMMISSION
Draw. DD Form Approved.
Budget Bureau No. 42-R1424

Artesia, NM 68210

5. LEASE

NM 01148

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Big Eddy Unit

8. FARM OR LEASE NAME

Big Eddy Unit

9. WELL NO.

95

10. FIELD OR WILDCAT NAME

Eddy Undesignated Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 33, T21S, R28E

12. COUNTY OR PARISH 13. STATE

Eddy New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3161' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 6-1/8" hole to 12,450' 10-16-82. Logging

Ran 28 jts. 4-1/2" 13.50# N-80 LT&C csg. & Liner Hanger. Set Liner @ 12,450'. T/Liner @ 11,342'.

Western cemented with 200 sx Class "H" cement with additives displaced with FW. Plug down @ 10:00 a.m. MST 10-17-82.

Reversed 40 sx cement. WOC 3-1/2 hrs. PU Halliburton FO cement tool. RIH to 2180'. Open FO tool & cemented with 300 sx Class "C" with additives displaced with FW. Closed FO tool & reversed out very little cement. POH with Halliburton Tool.

RIH with bit to 10,750'. WOC 6-1/2 hrs. FIH TOC @ 11,170' (172' over T/Liner).

Drill cement to T/Liner @ 11,342'. Test T/Liner to 2000 psi. OK. Had 9.4 ppg mud in hole. Displaced hole with FW. Rig released @ noon MDST 10-19-82.

Wait on Completion.

Subsurface Safety Valve: Manu. and Type

N/A

Set @ ----- Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED R. C. Anderson TITLE Sr. Prod. Clerk DATE 10-20-82

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL

(ORIG. SEC.) DAVID R. GLASS

OCT 21 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

RECEIVED

OCT 25 1982

O. C. D.
ARTESIA, OFFICE