UNITED STATES DERMAN DO

DEPARTMENT OF THE INTERIOR 12, NM **GEOLOGICAL SURVEY**

882105. LEASE NM-17103

	**** - / - 0		
6.	IF INDIAN,	ALLOTTEE OR	TRIBE NAME
		 	RECEIVED

						7 c' .	<u> </u>	KEC	-FIVE	<u>D</u>
SUNDRY NOTIC	CES AND REPORTS	ON WELLS	7.	UNIT AGI	REEME	NT N	AME :	N. O	# # Z	
(Do not use this form for pro	oposals to drill or to deepen or for such proposals.)	plug back to a different	8.	FARM OR	LEAS	É NAN	1E JA	11 2	4 19	3 3
				Lee Fe	$\operatorname{dera}^{\varsigma}$	i c	om		ξ. 	
1. oil gas well well	other Drilling	Well		WELL NO			- `	ESIA,	OFFIC	:E \
2. NAME OF OPERATO		ŀ	10	FIELD OF	_ ← P WII D	CATI	JAME	<u> </u>	# 7 E	
Liberty Oil &			md					-	表門裝	
3. ADDRESS OF OPER		77380 Tx.		SEC., T.,					URVEY	OR
<u>1776 Woodstead</u>	d Ct. Suite 200, T (REPORT LOCATION CLE	he Woodlands,		AREA	,			9		
	. (REPORT LOCATION CLL	ARET. See Space 17		S	ec.	25.	T209	. Ř	28E	
below.) AT SURFACE: 1	980' N&E		12.	COUNTY						
AT TOP PROD. INT				Eddy			1 '	N.M		
AT TOTAL DEPTH:			14.	API NO.		4.				
16. CHECK APPROPRIA	TE BOX TO INDICATE N	ATURE OF NOTICE,			<u>:</u>	· <u>: :</u>	•		<u> </u>	
REPORT, OR OTHE			15.	ELEVATI	ONS (SHOW			AND \	ND)
	== 0UBCEOUE	NT DEDORT OF		3240.8	31 GR	· <u></u>	,·	<u> </u>	, - ,	
REQUEST FOR APPROV	·	NT REPORT OF:			-	ੂੰ ਹੋਂ	i.	6 4 6 ±		
TEST WATER SHUT-OFF	·						<u>.</u>	ទួ		
FRACTURE TREAT SHOOT OR ACIDIZE	H E				2	1 7	ni tu		िर ए है। (च.)	
REPAIR WELL			(N	OTE: Repo				compl	etion or	zone
PULL OR ALTER CASIN	1G ☐			cnan	ge on F	orm 9	-330.)			
MULTIPLE COMPLETE							2.2	<u> </u>		
CHANGE ZONES ABANDON*	H E				-	f Fig.	£."	. 9)	
(other) Cem	ent and Casing	_		į.		S (,	
including estimated measured and true	SED OR COMPLETED OPER I date of starting any proper vertical depths for all mark ang point 32281.	ers and zones pertinents of the services and zones pertinents (3)	it to t	his work.)	9 5/	8# ;	36.0	o#,.	J-55	
	casing and set a				Ĕ.		1.1	<u> </u>	5 3 0	
lst	stage cement with	400 sx 65-35 p	00 Z –.	lite c	emen	L JO.	ΪΤΟΜ:	eu i	y ku	J DX
Clas	ss 'C' cement with	2% CaU1.			۶.	. దొక్ మం	0.60	2000	- 함성 : = 함성 :	
2nd	stage cement same	as first stage	e.	Cement	2nd	sta 900	ge w	ith	nost	eturns.
	temperature surve						1 1			Ė
111 (cement to surface	using 340 sx of	cl	ass ¹C	cei	nent	5. C:	irci	ilate	d
15 s	sx of cement to su	rface. POB 6:3	30 P	.M. 1/	15/8	3•	MOC 를	18 I	iours	•
Pres	ssure tested casin	g 1000 psi 30 m	ninu	tes.	Ţ.	진원	5 E	<u></u>		- ;
					ć.	ش ت : د	발 :	¥.	5 6 5 · ·	
Subsurface Safety Valve	e: Manu. and Type					Se	t @ =	1		Ft.
					-	<u>.</u>	i to	S .		<u> </u>
. //	t the foregoing is true and c				٦ /	21/8	3	et G		
SIGNED LUNG	W. Tranklen TIT	LEAgent		DATE _		21/0		. 19	6 6 3	
——————————————————————————————————————	CCEPTED FOR RECORD (This sp.	ce for Federal or State of	fice us	se)		4. E }		_ 	10 10 10 10 10 10 10 10 10 10 10 10 10 1	
(ORIG	G. SGD.) DAVID R. GI	İ		DATE				= :::	327	<u> </u>
APPROVED BY CONDITIONS OF APPROV		इटिह्यू			1	00 00 10 F	10 10 0 1	meti	Coodures Sept 1991 Coodures	· ·
	LS MANAGEMENT SERVICE	JAN 21 1983 e Instructions on Reverse	Side	}	Š	W 200	_	ů.	ā: D	