

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates Pet. Co.</u>		Lease <u>Stonewall Wm St.</u>		Well # <u>1</u>	
Location of Well	Unit <u>0</u>	Section <u>30</u>	Township <u>20S</u>	Range <u>28E</u>	County <u>Zddy</u>
Drilling Contractor <u>LaRue</u>	Type of Equipment <u>Rotary</u>				
<u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2"</u>	<u>13 3/8"</u>	<u>28#</u>	<u>New</u>	<u>600'</u>	<u>CIRC</u>
<u>* 12 1/4"</u>	<u>8 5/8"</u>	<u>24-28#</u>	<u>"</u>	<u>2650'</u>	<u>CIRC</u>
<u>7 7/8"</u>	<u>5 1/2"</u>	<u>17-20#</u>	<u>"</u>	<u>TD</u>	<u>150 SX</u>
Casing Data:					
Surface _____ joints of _____ inch _____ # Grade _____					
(Approved) (Rejected) _____					
Inspected by _____ date _____					
Cementing Program					
Size of hole <u>12 1/4</u> Size of Casing <u>8 7/8</u> Sacks cement required _____					
Type of Shoe used <u>Tex-Pat</u> Float collar used <u>Insert</u> Btm 3 jts welded _____					
TD of hole <u>2485</u> Set <u>2486</u> Feet of <u>8 7/8</u> Inch <u>24</u> # Grade <u>J-55</u>					
New-used csg. @ <u>2486</u> with <u>250</u> sacks neat cement around shoe					
+ <u>1100</u> sax <u>Hewco Lite</u> additives _____					
Plug down @ _____ (AM) (PM) Date _____					
Cement circulated <u>yes</u> No. of Sacks <u>150</u>					
Cemented by <u>Hewco</u> Witnessed by _____					
Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks: <u>Last Drilling Break 2286</u>					