

c/37

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other Drilling Well
2. NAME OF OPERATOR
Liberty Oil & Gas ✓
3. ADDRESS OF OPERATOR 77380 Tx.
1776 Woodstead Ct., Suite 200, The Woodlands
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1975' N & 1765' E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

- | | | |
|----------------------------------|--------------------------|--------------------------|
| TEST WATER SHUT-OFF | <input type="checkbox"/> | <input type="checkbox"/> |
| FRACTURE TREAT | <input type="checkbox"/> | <input type="checkbox"/> |
| SHOOT OR ACIDIZE | <input type="checkbox"/> | <input type="checkbox"/> |
| REPAIR WELL | <input type="checkbox"/> | <input type="checkbox"/> |
| PULL OR ALTER CASING | <input type="checkbox"/> | <input type="checkbox"/> |
| MULTIPLE COMPLETE | <input type="checkbox"/> | <input type="checkbox"/> |
| CHANGE ZONES | <input type="checkbox"/> | <input type="checkbox"/> |
| ABANDON* | <input type="checkbox"/> | <input type="checkbox"/> |
| (other) <u>Casing and Cement</u> | | <u>x</u> |

5. LEASE

NM-17103

6. IF INDIAN, ALLOTTEE OR TRIBE NAME **RECEIVED**

7. UNIT AGREEMENT NAME

MAR 17 1983

8. FARM OR LEASE NAME

Lee Federal

O. C. D.

9. WELL NO.

ARTESIA, OFFICE

10. FIELD OR WILDCAT NAME

Wildcat-Vates

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 25, T20S, R28E

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3239.9' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2/28/83 Spud 13" hole at 10:37 A.M.

3/04/83 Casing point 250'. Ran 6 joints(250') of 10 3/4", 40.5#, J-55, ST&C casing and set at 248'.

Cement with 115 sx of Class 'C', with 2% CaCl cement. Full circulation throughout job. Circulated 5 sx of cement to surface.

W.O.C. 18 hours. Found top of cement at 46'. Redi-mix cement to surface with 7 sx of cement.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED David R. Glass TITLE Agent DATE 3/15/83

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

(ORIG. SGD.) **DAVID R. GLASS**

DATE

MAR 15 1983

MINERALS MANAGEMENT SERVICE
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side

RECEIVED
MAR 15 1983

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO