

4/8/77

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

NM OIL CONS. COMMISSION

New Mexico DD

NM-17103

RECEIVED BY 88210

10. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

O.C.D.

ARTESIA OFFICE

2. NAME OF OPERATOR

Liberty Oil & Gas

3. ADDRESS OF OPERATOR

The Woodlands, Tx.

1776 Woodstead Ct., Suite 200, 77380

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1975' N & 1765' E

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH: Same

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Lee Federal

9. WELL NO.

3

10. FIELD OR WILDCAT NAME

Wildcat-Yates

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 25, T20S, R28E

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3239.9' GR

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☐

(other) Casing & Cement

RECEIVED
JUL 22 1983

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS

ROSWell, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3/23/83 Encountered fresh water zones at 254' and 450'. Prepare to run 7" casing. Ran 672' of 7", 23.5#, J-55 casing and set at 671'. Cement with 250 sx of Class C, 2% CaCl. Cement did not circulate. Ran temperature survey found TOC at 300'. Made 3 attempts to cement to surface with 125 sx of Class C, 2% CaCl. Ran 1" on outside of 7" casing and found TOC at 116'. 1" to surface with 30 sx of Class C cement. Circulated 5 sx of cement to surface. Job complete 3/26/83.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

J. W. Franklin

TITLE

Agent

DATE

7/21/83

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

AUG 23 1983

*See Instructions on Reverse Side