ENERGY AND MINERALS DEPARTMEN	1T				
		TION DIVISION			
h	P. O. BO				Form C-103
DISTRIBUTION			с. – К. <b>К</b>		Revised 10-1-78
BANTAFE V	SANTA FE, NEW	MEXICO BAROIT	- 	<u>)</u>	
PILE V		5 (B)	<b>ECEIVE</b>	. Indicate Typ	pe of Lease
U.S.O.S.		· .	T	State	Fee X
LAND OFFICE				5. State Oil & C	as Lease No.
OPERATOR /	JUN 2.9.19			33	
SUNDRY 100 NOT USE THIS FORM FOR PROP	NOTICES AND REPORTS ON	WELLS	v Č. D.		
1.		ARTE	SIA. OFFIC	E. Unit Agreem	nt Name
OIL X CAS	OTHER-				
Name of Operator				8. Farm or Lease Name	
MESA PETROLEUM CO.				Hondo Fee	
Address of Operator			9. Well No.		
P. O. Box 2009 / Amarillo, Texas 79189				2	
S. Location of Well				10. Field and Pool, or Wildcat	
UNIT LETTERK 1980 FELT FROM THE South LINE AND 1650 FEET FROM				Undes. Av	alon Delaware
UNIT LETTER	<u>Job Plly Prov the</u>	LINE AND		nnnn	
51	3.2 205	28F	ł	////////	
THE WEST LINE, SECTION	32 YOWHSHIP 20S	RANGE 201	NMPM.	////////	
		DC PT CP and		12. County	***********
15. Elevation (Show whether DF, RT, GR, etc.)					
	3210.1' GR			Eddy	
IL. Check A	ppropriate Box To Indicate N	ature of Notice, Repor	rt or Othe	r Data	
NOTICE OF IN	••••			REPORT OF	:
Notice of in			•		
	PLUG AND ABANDON	REMEDIAL WORK		ALTE	
PLAFORM BEMEDIAL WORK		COMMENCE DRILLING OPHS.	<b>T</b>		AND ABANDONMENT
I MPORABILY ABANDON		COMMENCE DRILLING OPHS.		200	
PULL OR ALTER CASING	CHANGE PLANS		പ		<b>۲</b>
	r	OTHER			LJ
OTHER	[]				
		ile and size particulated	includin	nimated data at	

ł

I

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1905.

Spudded well with 17 1/2" hole on 6-21-83. Drilled to 588' and ran 14 jts 13 3/8", 40#, N-40, ST&C, R-3, Class "C" casing set at 588'. Cemented with 630 sx "C" + 2% CaCl + 1/4# cello-flakes. PD at 2145 6-22-83. Circulated 100 sx. Bump plug with 300 psi - held for 8 hours. Reduced hole to 12" and drilled ahead on 6-24-83. WOC total of 25 1/4 hours. Drilled to 2422' and ran 58 jts 8 5/8", 24#, K55, ST&C casing set at 2422'. Cemented with 1150 sx BJ Lite + 5# Gilsonite + 2/10% D-6 + 1/4# cello-flakes and tailed in with 150 sx "C" + 2% CaCl + 1/4# cello-flakes. Circulated 80 sx. PD at 0545 6-26-83. Tested BOPs and casing to 800 psi for 30 min -- ok. Reduced hole to 7 7/8" and drilled ahead on 6-27-83. WOC total of 25 hours.

XC: NMOCD-A (0+2), CEN RCDS, ACCTG, MAT CONT, OPS(FILE), MIDLAND, ROSWELL, PARTNERS

18. I hereby certify that the information above is true and complet sicus R. E. Machine	REGULATORY COORDINATOR	6-28-83
APPROY[D B7	Original Signed By Leslie A. Clements TITLE <u>Supervisor District 11</u>	DATE JUN 2 9 1983
CONDITIONS OF APPROVAL, IF ANYS		