

RECEIVED BY	
DISTRIBUTION	
SANTA FE	☒
ALBUQUERQUE	☒
EL PASO	☐
ARTESIA	☐
OTHER	☒

OIL CONSERVATION DIVISION

P. O. BOX 2085

SANTA FE, NEW MEXICO 87501

RECEIVED BY
DEC 21 1983
O. C. D.
ARTESIA, OFFICE

FILE NO. **K-6854**
DATE **IX**

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR DEEP SALES. IT IS ONLY TO BE USED FOR WELLS THAT ARE NOT DEEP SALES.

OIL WELL ☒ GAS WELL ☐		7. City, Agent, and State	
1. Name of Operator Yates Petroleum Corporation		8. Field or Lease No. Stonewall WM State	
2. Address of Operator 207 South 4th St., Artesia, NM 88210		9. Well No. 2	
3. Location of Well ONLY LETTER P 480 FEET FROM THE South LINE AND 990 FEET FROM East LINE, SECTION 30 TOWNSHIP 20S RANGE 28E NMEN.		10. Field and Pool, or Section Und. Avalon Delaware	
4. Elevation (Show whether DT, RT, GA, etc.) 3243' GR		11. County Eddy	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PREPARE SPECIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
PERMANENTLY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OTHER ☐	PLUG AND ABANDONMENT ☐
GET OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☐	
OTHER <u>Production Casing, Perforate, Acidize</u> ☒			

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any production) SEE RULE 1103.

TD 4962'. Ran 111 jts 5-1/2" 15.5# J-55 casing set 4962'. 1-regular guide shoe set 4962'. Float collar set 4916'. Cemented w/750 sx Class C, .6% CF-1, 5#/sx salt. Compressive strength of cement - 950 psi in 12 hrs. PD 11:30 PM 10-14-83. Bumped plug to 1000 psi, released pressure and float held okay. WOC. WIH and perforated 2941-45' w/5 .50" holes (1 SPF). RIH w/packer and tubing. GIH to 2945', spot 1 bbl acid. POOH to 2866' and set packer. Acidized perms 2941-45' w/3000 gallons 7 1/2% MOD 101 acid and ball sealers. Swabbed well. No show of oil or gas. TOH w/tubing and packer. GIH w/cement retainer and set at 2909'. Squeezed perms 2941-45' w/100 sacks Class C, .6% CF-1, .2% AF-S and 5#/sack salt. Pull out of retainer. WIH and perforated 2698-2744' w/14 .42" holes as follows: 2698, 2700, 02' (2 SPF); 1720, 21' (2 SPF); 2738, 40, 42, 44' (1 SPF). GIH w/packer to 2744' and spot 1 bbl acid. POH to 2627' and set packer. Acidized perms 2698-2744' w/6000 gallons MOD 101 acid and ball sealers. Swabbed well. No show of oil or gas.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Leslie A. Clements</u>	TITLE <u>Production Supervisor</u>	DATE <u>12-20-83</u>
PROVED BY _____	TITLE <u>Original Signed By</u> <u>Leslie A. Clements</u> <u>Supervisor District II</u>	DATE <u>DEC 21 1983</u>

CONDITIONS OF APPROVAL, IF ANY: