

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

OIL CONSERVATION DIVISION

P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

RECEIVED BY

SEP 02 1983

O. C. D.  
ARTESIA, OFFICE

Form C-103  
Revised 10-1-78

Indicate Type of Lease

State ☒

Fee ☐

U.S. State Oil & Gas Lease No.

K-6854

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.

OIL WELL ☒

GAS WELL ☐

OTHER ☐

Name of Operator

Yates Petroleum Corporation ☒

Address of Operator

207 South 4th St., Artesia, NM 88210

Location of Well

UNIT LETTER M 330 FEET FROM THE South LINE AND 990 FEET FROM

THE West LINE, SECTION 30 TOWNSHIP 20S RANGE 28E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name

Stonewall WM State

9. Well No.

4

10. Field and Pool Name

Und. Avalon Delaware

15. Elevation (Show whether DF, RT, GR, etc.)

3285' GR

12. County

Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

CHANGE PLANS ☐

CASING TEST AND CEMENT JOBS ☒

OTHER ☐

3. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 17-1/2" hole 4:00 PM 8-29-83. Set 40' of 20" conductor pipe. Ran 14 joints 13-3/8" 54.5# K-55 ST&C casing set 535'. 1-Texas Pattern notched guide shoe set 535'. Insert float set 498'. Cemented w/500 sacks Class "C" 1/4# celloseal and 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hours. PD 12:30 PM 8-31-83. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 40 sacks. WOC. Drilled out 12:30 AM 9-1-83. WOC 12 hours. Cut off and welded on flow nipple. Reduced hole to 12-1/4". Drilled plug and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Leslie A. Clements

TITLE Production Supervisor

DATE 9-2-83

Original Signed By

Leslie A. Clements

Supervisor District II

APPROVED BY

TITLE

DATE

SEP 02 1983

CONDITIONS OF APPROVAL, IF ANY: