

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

OIL CONSERVATION DIVISION
P. O. BOX 20888
SANTA FE, NEW MEXICO 87501
RECEIVED BY
SEP 21 1983
O. C. D.
ARTESIA, OFFICE

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K-6854

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
Name of Operator Yates Petroleum Corporation	8. Farm or Lease Name Stonewall "WM" St.
Address of Operator 207 S. 4th St., Artesia, NM 88210	9. Well No. 5
Location of Well UNIT LETTER <u>K</u> <u>1650</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>West</u> LINE, SECTION <u>30</u> TOWNSHIP <u>20s</u> RANGE <u>28e</u> NMPM.	10. Field and Pool, or Wildcat <u>Undes. Avalon Delaware</u>
11. Elevation (Show whether DF, RT, GR, etc.) 3284' GL	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 17-1/2" hole 5:00 pm 9-15-83. Ran 14 joints of 13-3/8" 54.5# J-55 casing set at 535'. 1-regular guide shoe set at 535'. Baffle plate set at 495'. Cemented with 600 sacks Class "C", 1/4#/sack flocele and 2% CaCl₂. Compressive strength of cement - 1250 psi in 12 hours. PD 7:00 am 9-17-83. Bumped plug to 750 psi, released pressure and float held okay. Cement circulated 50 sacks to pit. WOC. Drilled out at 7:00 pm 9-17-83. WOC 12 hours. Cut off and welded on flow nipple. Reduced hole to 12-1/4". Drilled plug and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Leslie A. Clements TITLE Production Supervisor DATE 9-20-83

APPROVED BY Original Signed By Leslie A. Clements TITLE Supervisor District II DATE SEP 26 1983
CONDITIONS OF APPROVAL, IF ANY: