

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates</u>		Lease <u>Stonewall YE ST.</u>		Well # <u>1</u>	
Location of Well	Unit <u>I</u>	Section <u>30</u>	Township <u>20</u>	Range <u>28</u>	County <u>EDDY</u>
Drilling Contractor	<u>LARUE DRLLNG. 2</u>		Type of Equipment <u>ROTARY</u>		

\* Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17 1/2"	13 3/8"	48#	NEW	550'	CIRC.
* 12 1/4"	8 5/8"	24-28#	"	2500'	CIRC.
7 7/8"	5 1/2"	17-20#	"	TD	(650) TIE BACK TO 8 5/8

Casing Data:

Surface \_\_\_\_\_ joints of \_\_\_\_\_ inch \_\_\_\_\_ # Grade \_\_\_\_\_

(Approved) (Rejected)

Inspected by \_\_\_\_\_ date \_\_\_\_\_

Cementing Program

Size of hole 12 1/4 Size of Casing 8 5/8 Sacks cement required \_\_\_\_\_

Type of Shoe used Tex-Pac Float collar used Insert Btm 3 jts welded yes

TD of hole 2415 Set 2420 Feet of 8 5/8 Inch 24 # Grade J-55

New-used csg. @ 2420 with 400 sacks neat cement around shoe

+ 450 sack ~~Western~~ Western lite additives 1/4 Flo Seal 3% CC

Plug down @ 5:30 (AM) (~~PM~~) Date 10-24-83

Cement circulated yes No. of Sacks 1.5

Cemented by Western Witnessed by \_\_\_\_\_

Temp. Survey ran @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_ top cement @ \_\_\_\_\_

Casing test @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method Used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Checked for shut off @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Remarks: \_\_\_\_\_