STATE OF NEW MEXICO -			•
ENERGY AND MINERALS DEPARTMENT	OH CONSERVAT	TON DIVISION.	
DISTRIBUTION	OIL CONSERVAT		Form C-103 .
SANTA FE	SANTA FE. NEW I	1EXICO 87501	Revised 10-1-78
PILE WV		1 EXINOV 3581 1983	Sa. Indicate Type of Lease
U.S.O.S.			State X Foe
LAND OFFICE		O. C. D.	5, State Otl & Gas Lease No.
OPERATOR /		ARTESIA, OFFICE	K-5115
SUNDRY NOT	ICES AND REPORTS ON W	FILS	
SUNDRY NOTICES AND REPORTS ON WELLS 100 NOT USE THIS FORM FOR PROPOSALS TO CRILL OR TO DELPTH OR PLUG BACK TO A DIFFERENT RESERVOIR. 100 NOT USE THIS FORM FOR PERMIT -" CONTINUE OF DELPTH OR PROPOSALS."			
			7, Unit Agreement Name
OIL X GAB WELL OTHE	R.	•	
Name of Operator			8. Farm or Lease Name
Yates Petroleum Corporation 🗸			Stonewall EP State
207 So. 4th St., Artesia, NM 88210			9. Well No.
			10. Field and Pool, or Wildcat
E 2310	North	990	Und. Avalon Delaware
UNIT LETTER	North North	LINE AND FEET PRO	
Hook 20	200	2017	
THE West LINE, SECTION 30	TOWNSHIP 205	RANGE ZOL NMP	~()
	15. Elevation (Show whether Di	F, RT, GR, etc.)	12. County
	3314' GR		Eddy
Check Approp	· L	ture of Notice, Report or C	
NOTICE OF INTENT		•	NT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON		COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING	CHANGE PLANS	CASING TEST AND CEMENT JOB X	
		OTHER	
OTHER			
17. Describe Proposed or Completed Operations	(Clearly state all pertinent detail	s, and give persinent dates, includi	ng estimated date of starting any proposed
work) SEE RULE 1103.			
Spudded 17-1/2" hole 1:30 PM	11-20-83. Lost circ	culation at 87'. Spot	ted 10 yards of Ready-
Mix at 100'. Drilling 490' with no returns. Ran 13 joints of 13-3/8" 48# J-55 casing set			
544'. 1-Texas Pattern notch			
sacks Class "C" 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hours. PD 1:30			
PM 11-22-83. Bumped plug to	1000 psi, released p	ressure and float hel	d okay. Cement did
not circulate. WOC 6 hours.	Ran Temperature Sur	vey and tagged cement	inside casing. Cemented
to top of casing with 50' Re	ady Mix. WOC. Drill	led out 1:30 AM 11-23-	83. WOC 12 hours.
Cut off and welded on flow n Drilled plug and resumed dri		g to 1000 psi for 30 m	inutes, OK. Reduced hole
Diffied plug and resumed diff	iiing.		
8. I hereby certify that the information above is	true and complete to the best of	my knowledge and belief.	
11 - 2.	,		
IGHE HI and a boil	CCH TITLE Pr	oduction Supervisor	DATE 11-29-83
// 		Original Signed By	
•		Loslie A. Clements	NOV 3 0 198 3