ENERGY AND MINERALS DEPARTM	ENT		
	OIL CONSERVATI	ON REVENCENBY	
DISTRIBUTION	Р. О. ВОХ 2		Form C-103
BANTAFE	SANTA FE, NEW M		Revised 10-1-75
FILE	1	<b>DEC</b> PZ 1983	Sa. Indicate Type of Lesse
U.S.G.S.			
LAND OFFICE		• O. C. D.	State X Foe
OPERATOR	]	ARTESIA, OFFICE	5. State Off 6 Gas Lease No. K-5115
USE "APPLICA	RY NOTICES AND REPORTS ON WE	LLS	2. Unit Agrees ent Nane
	OTHER-		
Yates Petroleum Corporation			8. Form of Lease Name Stonewall EP State
Address of Coverator 207 South 4th St., Artesia, NM 88210			9. Well No. 5
Location of Well			10, Field and Pool, or Wildcat
Е	2310 rest from the North	بيرل 099	, Avalon Delaware
UNIT LETTER	FELT FROM THE	LINE AND FEET FAION	
West	30 20S	28E	$\chi(\chi(\chi(\chi(\chi(\chi(\chi(\chi(\chi(\chi(\chi(\chi(\chi(\chi(\chi(\chi(\chi(\chi(\chi($
. MTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTT			12. County
	3314' GR		Eddy
Check	Appropriate Box To Indicate Natu	re of Notice. Report or Otl	her Data
	NTENTION TO:	· •	REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON RE	MEDIAL WORK	ALTERING CASING
ILMPORARILY ABANDON	cc	IMMENCE ORILLING OPHS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING	CHANGE PLANS CA	SING TEST AND CEMENT JOB	
		OTHER Intermediate Ca	sing [X]
OTHER			

2. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 2420'. Ran 60 jts of 8-5/8" 24# K-55 ST&C 8rd casing set at 2420'. 1-Texas Pattern notched guide shoe set 2420'. Insert float set 2380'. Cemented w/800 sacks Class C, 4% gel, 5#/sack Hiseal and 2% CaCl2. Tailed in w/350 sacks Class C 2% CaCl2. PD 2:00 AM 11-27-83. Bumped plug to 1000 psi for 30 minutes, released pressure and float held okay. Cement did not circulate. Bond log indicated cement top at approx. 900'. Ran 1". Tagged cement at 851'.Filled hole w/50 bbls water. Spotted 150 sacks Class C Neat. PD 9:45 PM 11-28-83. WOC 3-1/2 hrs. Ran 1". Tagged cement at 504'. Spotted 300 sacks Class C Neat. PD 2:20 AM 11-29-83. Cement circulated 10 sacks. WOC. Drilled out at 2:30 PM 11-29-83. WOC 60 hrs and 30 minutes. NU and tested to 1000 psi for 30 minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

o. I hereby certify that the information above is true and complet idness and anita Dodlest	e to the best of my knowledge and belief. THTLE Production Supervisor Griginal Signed By	DATE 12-12-83
	Leslie A. Clements Supervisor District II	DEC. 1. 2. 1983

ONDITIONS OF APPROVAL, IF ANYI