

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-76

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

5a. Indicate Type of Lease:
State ☒ Fee ☐
5. State Oil & Gas Lease No.
K-5115

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "NOTIFICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

RECEIVED BY

JAN 06 1984

O. C. D.

ARTESIA, OFFICE

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator
Yates Petroleum Corporation ✓
Address of Operator
207 South 4th St., Artesia, NM 88210

7. Unit Agreement Name
8. Farm or Lease Name
Stonewall EP State
9. Well No.
5

Location of Well
UNIT LETTER E 2310 FEET FROM THE North LINE AND 990 FEET FROM
THE West LINE, SECTION 30 TOWNSHIP 20S RANGE 28E NMPM.

10. Field and Pool, or Whichever
Avalon Delaware

15. Elevation (Show whether DF, RT, GR, etc.)
3314' GR

12. County
Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data.
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☒ Production Casing, Perforate, Treat

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 4870'. Ran 118 jts of 5-1/2" 15.5# J-55 casing set 4870'. 1-regular guide shoe set 4870'. Float collar set 4830'. Cemented w/800 sacks Class "C", .6% CF-1, 5#/sack salt, .2% AF-S. Compressive strength of cement - 950 psi in 12 hrs. PD 1:30 PM 12-6-83. Bumped plug to 1000 psi for 30 minutes, released pressure and float held okay. WOC 18 hours. WIH and perforated 4336-46' w/4 .41" holes as follows: 4336, 38, 44 and 46'. Acidized perms 4336-46' w/1500 gal 7 1/2% MOD 101 acid and ball sealers. WIH and perforated 4252-4304' w/11 .40" holes as follows: 4252, 53, 54, 4271, 72, 73, 4292, 96, 98, 4302 and 04'. Acidized perms 4252-4304' w/4000 gal 7 1/2% MOD 101 acid and ball sealers. WIH and perforated 4142-83' w/12 .40" holes as follows: 4142, 46, 48, 51, 60, 65, 68, 72, 75, 77, 80, and 83'. Acidized perms w/3500 gal MOD 101 acid and ball sealers. Swabbing well.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed Leslie A. Clements

TITLE Production Supervisor

DATE 1-4-84

Original Signed By

Leslie A. Clements

APPROVED BY _____

TITLE Supervisor District II

DATE JAN 10 1984

CONDITIONS OF APPROVAL, IF ANY: