## INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-diffed or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, liens 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

## INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

## Northwestern New Mexico

т.	Anhy	T.	Canyon	T		Ojo Alamo	T. T	Penn. "B"
т.	Salt	Т.	Strawn	T		Rintland-Fruitland	т. Т	Penn. "C"
B.	Salt 464	Т.	Atoka	T		Pictured Cliffs	1. T	Penn. "D"
T.		T.	Miss	T	•	Cliff House	і. т	Leadville
т.	7 Rivers	Т.	Devonian	1		Mencice	1. T	Madison
Τ.	Queen	Т.	Silurian			Point Lookout	1. T	Elbert
Τ.	Grayburg	Τ.	Montoya	Т		Mancos	1. T	McCracken
T.	San Andres	T.	Simpson	T		Gallup	. I. 	Ignacio Qtzte
Т.	Glorieta	Т.	McKee	E	as	e Greenhorn	1. T	Granite
т.	Paddock	Т.	Ellenburger		•	Dakota	1. T	
т.	Blinebry	. Т.	Gr. Wash	T		Morrison	Т.	
т.				<u> </u>		Todilto	. I. 	
Τ.	Drinkard	Т.	Delaware Sand	407 1 820 1	ľ.	Entrada	Т. т	
Т.	Аьо	<b>. T</b> .	Hone Sonnes			Wingate	. 1.	
T.	Wolfcamp	<b>. T</b> .		า	ſ.	Chinle	. Т.	
Т.	Penn	. <b>T</b> .		T	Γ.	Pennian	. T.	<u></u>
т	Cisco (Bough C)	Т.			٢.	Penn. "A"	. Т.	
			OIL O	R GAS	SA	NDS OR ZONES		
No.	1, from		_to		No.	. 4, from	•••••	to
No.	2, from		to		٩o.	. 5, from	*****	to
No.	S, frora	••••	.to		No.	. 6, from	•••••	to

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

.

. .

Southeastern New Mexico

No. 1, frorafee	t
No. 2, fromfee	t
No. 3, fromfee	<b>t.</b>
No. 4, from	t

FORMATION RECORD (Attach additional sheets if necessary)

From To		Thickness in Feet	Formation	From	То	Thickness in Feet	Formation
0	540	540	Surface, Redbeds, Anydrite				
540	850	310	Anhydrite, Dolomite, Sand				
850	1050	200	Dolomite, Anhydrite				
1050	1750		Dolomite				
1750	2124		Dolomite, Sand		·		
2124	2454		Dolomite				
2454	2534		Sandstone, Dolomite				
2534	2586		Chert, Dolomite, Sand				
2586	2916	330	Sandstone, Dolomite			1	
2916	3124	208	Sandstone, Dolomite, Shale				
3124	3180	56	Dolomite				
3180	3340	160	Sandstone				
3340	4464	1124	Sandstone, Shale				
4464	4780	316	Shale, Sand				
4780	4870	90	Shale, Sand, Lime				