

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	☒
FILE	☒
U.S.G.S.	
LAND OFFICE	
OPERATOR	☒

OIL CONSERVATION DIRECTOR
P. O. BOX 208
SANTA FE, NEW MEXICO 87501

DEC 14 1983

O. C. D.
ARTESIA, OFFICEForm C-103
Revised 10-1-78

a. Indicate Type of Lease

State ☒For ☐

b. State Oil & Gas Lease No.

K-5115

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)OIL
WELL ☒GAS
WELL ☐OTHER ☐

Name of Operator

Yates Petroleum Corporation ✓

Address of Operator

207 South 4th St., Artesia, NM 88210

Location of Well

UNIT LETTER D 990 FEET FROM THE North LINE AND 990 FEET FROM
THE West LINE, SECTION 30 TOWNSHIP 20S RANGE 28E N.M.P.M.

7. Unit Agreement Name

8. Farm or Lease Name

Stonewall EP State

9. Well No.

7

10. Field and Pool, or Wildcat
Und. Avalon Delaware

11. Elevation (Show whether DF, RT, GR, etc.)

3295' GR

12. County

Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐CHANGE PLANS ☐FULL OR ALTER CASING ☐OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐COMMENCE DRILLING OPNS. ☒CASING TEST AND CEMENT JOB ☒OTHER ☐ALTERING CASING ☐PLUG AND ABANDONMENT ☐

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 17-1/2" hole 9:30 AM 12-9-83. Set 40' of 20" conductor pipe. Ran 15 jts of 13-3/8" 68# J-55 ST&C casing set 538'. 1-Texas Pattern notched guide shoe set 538'. Insert flapper float set 509'. Cemented w/500 sacks Class "C" 2% CaCl₂. Compressive strength of cement - 1250 psi in 12 hrs. PD 5:15 PM 12-10-83. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 45 sacks. WOC. Drilled out 5:15 AM 12-11-83. WOC 12 hrs. Cut off and welded on flow nipple. Tested casing to 1000 psi for 30 minutes, OK. Reduced hole to 12-1/4". Drilled plug and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signature Leslie A. Clements TITLE Production SupervisorDATE 12-13-83

Original Signed By

Leslie A. Clements

APPROVED BY

TITLE Supervisor District II

DATE

DEC 14 1983

CONDITIONS OF APPROVAL, IF ANY: