

|                    |  |
|--------------------|--|
| DATE OF COMPLETION |  |
| DATE OF REPORT     |  |
| DATE OF WELL       |  |
| DATE OF CLOSURE    |  |
| DATE OF RE-ENTRY   |  |

CIT. CONFIRMATION OF RECEIVED BY

P. O. BOX 2000  
SANTA FE, NEW MEXICO

DEC 21 1983

O. C. D.  
ARTESIA, OFFICE

K-5115

SUNDAY NOTICES AND REPORTS

(DO NOT USE THIS FORM FOR A WELL THAT IS BEING DRILLED OR RE-ENTERED. IT IS FOR A WELL THAT IS BEING ABANDONED OR CLOSURE.)

CR ☒ CAS ☐

Yates Petroleum Corporation  
207 South 4th St., Artesia, NM 88210

Stonewall EP State

6. Well No. 7

Und. Avalon Delaware

D 990 North 990  
West 30 Township 20S Range 28E

3295' CR

Eddy

Check Appropriate Box To Indicate Nature of Action, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

|                                                |                                           |                                                                |                                             |
|------------------------------------------------|-------------------------------------------|----------------------------------------------------------------|---------------------------------------------|
| TEMPERATURE SURVEY <input type="checkbox"/>    | PLUG AND ABANDON <input type="checkbox"/> | REMEDIATION WORK <input type="checkbox"/>                      | ALTERING CASING <input type="checkbox"/>    |
| TEMPORARILY ABANDON <input type="checkbox"/>   | CHANGE PLANS <input type="checkbox"/>     | CONDUCT DRILLING OPS. <input type="checkbox"/>                 | PLUG AND REABANDON <input type="checkbox"/> |
| FULLY RE-ENTER CASING <input type="checkbox"/> |                                           | CASING TEST AND CEMENT JOB <input type="checkbox"/>            |                                             |
| OTHER <input type="checkbox"/>                 |                                           | CENTER Intermediate Casing <input checked="" type="checkbox"/> |                                             |

Describe Production or Completion Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any production) SEE REG. 1100.

Ran 58 jts of 8-5/8" 24# J-55 casing set 2372'. 1-Texas Pattern notched guide shoe set 2372'. Insert float set 2331'. Cemented w/500 sacks Class C 4% gel, 3#/sack Hiscal, 2% CaCl2. Tailed in w/450 sacks Class C 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hours. PD 2:15 AM 12-15-83. Bumped plug to 1000 psi, released pressure and float held okay. Cement did not circulate. WOC 6 hours. Ran Temperature Survey and found top of cement - 360'. Ran 1". Tagged cement 366'. Spotted 170 sacks Class C 3% CaCl2. PD 9:30 Am 12-15-83. Circulated 10 sacks. WOC. Drilled out 8:30 PM 12-15-83. WOC 18 hours and 15 minutes. Nipped up and tested to 1000# for 30 minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

ILLECIBLE

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Leslie A. Clements TITLE Production Supervisor DATE 12-20-83

APPROVED BY \_\_\_\_\_ TITLE Original Signed By  
Leslie A. Clements DATE DEC 21 1983  
Supervisor District II

CONDITIONS OF APPROVAL, IF ANY: