

EXXON CORPORATION - YATES FEDERAL "C" 35
 Section 5, T21S, R27E
 Eddy County, New Mexico
 BLM Eight Point Plan
 May 1991

1. The Estimated Tops of Important Geologic Markers (Note: All depths in this plan are expressed in feet).

<u>Formation</u>	<u>Tops</u>
Delaware Mt Group	2607'

2. The estimated depths at which the top and the bottom of anticipated water, oil, gas or other mineral bearing formations are expected to be encountered.

	<u>Top</u>	<u>Bottom</u>	<u>How Protected</u>
Delaware Sand	2607'	3110'	Production casing - cemented to surface.

Note: Since this is a re-entry of an existing well, all mineral/water bearing formations above the objective formation are protected by existing casing strings which have been cemented to surface.

3. Minimum Specifications for Pressure Control Equipment.

A. Wellhead and X-mas tree equipment:

"A" Section - 8-5/8" 8RD x 11" 2,000 psi WP
 "B" Section - 5-1/2" 8RD x 2-7/8" 2,000 psi WP

Injection X-mas tree will consist of a stainless steel 2,000 psi W.P. gate valve.

B. Blowout preventer equipment:

<u>Type</u>	<u>Pressure Rating</u>	<u>Installed on Casing</u>
RR BOP	2,000 psi	5-1/2"

Additional preventers may be added and/or preventers with higher pressure ratings may be substituted depending on equipment provided by service unit contractor. Diagram of the BOP equipment is attached.