

AUXILIARY EQUIPMENT

| | |
|-------------------------|--|
| DRAWWORKS | BDW 650M 650 HP, with PARMAC Hydromatic Brake. |
| ENGINES | Two Caterpillar D-353 diesels rated at 425 HP each. |
| ROTARY | Ideco 23", 300 ton capacity. |
| MAST/SUB | Ideal 132', 550,000 lb rated static hook load with 10 lines. Wagner 15' high substructure. |
| TRAVELLING EQUIPMENT | Gardner-Denver, 300 ton, 5 sheave w/ BJ 250 ton hook. Brewster Model 7 SX 300 ton swivel. |
| PUMPS | Continental-EMSCO DC-700 and DB-550, 5-1/2" X 16" Duplex, Compound driven. |
| PIT SYSTEM | 1-Shale Pit 6'X 7'X 35', 1-Settling Pit 6'X 7'X 34' w/ 5 mud agitators. Two centrifugal mud mixing pumps and a Double Screen Shale Shaker. |
| LIGHT PLANT | Two CAT 3306 diesel electric sets 180 KW prime mover. |
| BOP EQUIP | 13-5/8" 5000 psi WP double ram and 13-5/8" 5000 psi. WP Shaffer Annular Preventer. Choke manifold rated at 5000 psi. Valvcon 5-station 80 gallon closing unit. |

Exhibit D
Santa Fe Energy Operating Partners,L.P.
Nagooltee Peak "5" Federal Com. No.1
Section 5, T-22S, R-24E
Eddy County, New Mexico

DDR:NAGPEAK.PMT