

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR  
Yates Petroleum Corporation

3. ADDRESS OF OPERATOR  
207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
1980 FNL & 1980 FWL, Sec. 11-20S-29E  
AT SURFACE:  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

(other) Lost circulation plugs.

5. LEASE  
NM 15881

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Slinkard UR Federal

9. WELL NO.  
2

10. FIELD OR WILDCAT NAME  
Undes. Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Unit F, Sec. 11-T20S-R29E

12. COUNTY OR PARISH  
Eddy

13. STATE  
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3300' GR

RECEIVED BY

MAY 11 1984

O. C. D.  
ARTESIA, OFFICE

Report results of multiple completion or zone change on Form 9-330.)

RECEIVED  
BUREAU OF OIL & GAS  
ROSEMOUNT, ARIZONA  
JAN 18 9 22 AM '84

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded 17-1/2" hole at 9:00 PM 12-28-83. Lost returns at 323'. Before running 13-3/8" casing, set lost circulation plugs as follows:

Plug #1: Spotted 50 sacks Class C 3% CaCl<sub>2</sub> thru open ended drill pipe at 250'. PD 3:00 AM 12-31-83. WOC 3 hrs.

Plug #2: Spotted 50 sacks Class C 3% CaCl<sub>2</sub> thru open ended drill pipe at 250'. PD 6:14 AM 12-31-83. Plug set at 250'. WOC 3 hrs.

Plug #3: Spotted 100 sacks Class C 3% CaCl<sub>2</sub> thru open ended drill pipe at 120'. PD 9:45 AM 12-31-83. Plug set at 120'. WOC 7 hrs. Tagged cement at 120'.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Diana Doodler TITLE Production Supervisor DATE 1-17-84

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY AWO TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY  
MAY 9 1984

Carlsbad NEW MEXICO

\*See Instructions on Reverse Side