

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR
Yates Petroleum Corporation
3. ADDRESS OF OPERATOR
207 South 4th St., Artesia, NM 88210
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
1980 FNL & 1980 FWL, Sec. 11-20S-29E
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

- REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:
- | | | |
|----------------------|--------------------------|-------------------------------------|
| TEST WATER SHUT-OFF | <input type="checkbox"/> | <input checked="" type="checkbox"/> |
| FRACTURE TREAT | <input type="checkbox"/> | <input type="checkbox"/> |
| SHOOT OR ACIDIZE | <input type="checkbox"/> | <input type="checkbox"/> |
| REPAIR WELL | <input type="checkbox"/> | <input type="checkbox"/> |
| PULL OR ALTER CASING | <input type="checkbox"/> | <input type="checkbox"/> |
| MULTIPLE COMPLETE | <input type="checkbox"/> | <input type="checkbox"/> |
| CHANGE ZONES | <input type="checkbox"/> | <input type="checkbox"/> |
| ABANDON* | <input type="checkbox"/> | <input type="checkbox"/> |
| (other) | | |

5. LEASE
NM 15881
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Slinkard UR Federal
9. WELL NO.
2
10. FIELD OR WILDCAT NAME
Undes. Morrow
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Unit F, Sec. 11-T20S-R29E
12. COUNTY OR PARISH
Eddy
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3300' GR

RECEIVED
JAN 18 9 22 AM '84
BUREAU OF LAND MANAGEMENT
ROSWELL DISTRICT

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Note: Change surface casing from 640' to 350'.

Spudded 17-1/2" hole 9:00 PM 12-28-83. Ran 6 jts of 13-3/8" 48# ST&C casing set 200'. 1-Texas Pattern notched guide shoe set at 200'. Insert float set 157'. Cemented w/ 250 sx Thixolite, 1/4#/sx celloseal, 1#/sx Permacheck and 2#/sx Hiseal. Tailed in w/ 250 sx Class C, 1/4#/sx celloseal and 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hrs. PD 9:15 PM 1-4-84. Bumped plug to 750 psi, released pressure and float held okay. Cement did not circulate. WOC 4-1/2 hrs. Ran Temperature Survey and did not find top of cement. Ran 1". Tagged cement 120'. Spotted 50 sx Class C 3% CaCl2. PD 2:06 PM 1-4-84. WOC 1 hr. Ran 1". Tagged cement at 97'. Spotted 50 sx Class C 3% CaCl2. PD 3:06 PM 1-4-84. WOC 2-1/2 hrs. Ran 1". Tagged cement at 75'. Spotted 50 sx Class C 3% CaCl2. PD 5:45 PM 1-4-84. WOC 3 hrs. Ran 1". Tagged cement at 75'. Spotted 50 sx Class C 3% CaCl2. PD 8:15 PM 1-4-84. WOC 2 hrs. Ran 1". Tagged cement at 75'. Spotted 50 sx Class C 3% CaCl2. PD 10:15 PM 1-4-84. WOC 2 hrs. Ran 1". Tagged cement at 75'. Spotted 50 sx Class C 3% CaCl2. PD 2:50 AM 1-5-84. WOC 2 hrs.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

(continued page 2)

18. I hereby certify that the foregoing is true and correct

SIGNED Antonio Goodlett TITLE Production Supervisor DATE 1-17-84

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY SWP TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY

MAY 9 1984

Carlsbad,

NEW MEXICO *See Instructions on Reverse Side