

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE*
(Other instructions reverse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM 28145

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Loafer Draw Federal

9. WELL NO.

1

10. FIELD AND POOL OR WILDCAT

Rocky Arroyo-Morrow

11. SEC., T., E., M., OR BLK. AND SURVEY OR AREA

Unit B, Sec. 28-T21S-R22E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER Plugback and Recomplete

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

105 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

925' FNL & 2224' FEL, Sec. 28-T21S-R22E JUL 27 '88

14. PERMIT NO.

API #30-015-24746

15. ELEVATIONS (Show whether DF, RT, OR)

4408' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Plugback, perforate, trt

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

X

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Set CIBP at 8700' w/35' cement cap. Perforated Strawn 8363-8375', 8014-8018' and 7861-7868' (1 SPF) Total 26 .50" holes.

Acidized perfs 8363-8375' (13 holes) w/1500 gals 7½% MS acid and 12 ball sealers.

Acidized perfs 8014-8018' (5 holes) w/500 gals 7½% MS acid and 4 ball sealers.

Acidized perfs 7861-7868' (8 holes) w/1000 gals 7½% MS acid and 7 ball sealers.

Began work 6-8-88.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Production Supervisor

DATE 6-9-88

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

JUL 25 1988

*See Instructions on Reverse Side