

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

OIL CONS COMMISS-  
Drawer DD  
Artesia, NM 88210

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

5. Lease Designation and Serial No.  
NM-28145

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Loafer Draw Federal #1

9. API Well No.

30-015-24746

10. Field and Pool, or Exploratory Area

Und. Permo Penn

11. County or Parish, State

Eddy, NM

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

925' FNL & 2224' FEL of Section 28-T21S-R22E (Unit B, NWNE)

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☒ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Propose to recompleat well to Permo Penn as follows:

1. Nipple up BOP. Unset Lokset packer at 6800'. TOOH with packer and tubing.
2. Run GR/CCL/CBL log from 6300' to TOC to verify location of TOC. NOTE: If top of cement does not cover perforated interval, decision may be made to plug and abandon.
3. Perforate 5664-6044' w/46 holes (2 SPF) as follows: 5664, 65, 76, 78 & 5680 (10 holes); 5717, 19, 23 & 5728' (8 holes); 5770, 72 & 5774' (6 holes); 5814, 16, 34, 36, 38 & 5840' (12 holes) and 6032, 34, 40, 42 & 6044' (5 holes).
4. Straddle acidize perforations 5664-6044'.
5. Flow/swab back and test.

APR 21 1995

OIL CON. DIV.  
DIST. 2

14. I hereby certify that the foregoing is true and correct

Signed

*Joe G. Lara*

Title Production Clerk

Date March 23, 1995

(This space for Federal or State office use)

Approved by

(ORIG. SGD.) JOE G. LARA

Title

Petroleum Engineer

Date

4/19/95

Conditions of approval, if any: