Facer 0 221		Drawor DD		c)
Form 9-331	UNITED STA	Artesia, HN SUBMIT I	882. N TRIPLICATE•	Form approved.
(May 1963) DEF		IE INTERIOR (Other instant	structions on re-	Budget Bureau No. 42-R142 5. LEASE DESIGNATION AND SERIAL NO.
	GEOLOGICAL	SURVEY		NM 12241-A
SUNDRY	NOTICES AND R	EPORTS ON WELLS		G. 1F INDIAN, ALLOTTEE OR TRIBE NAME
		eepen or plug back to a different	reservoir.	
1. 011 C (115 C)	· ·	RECEIVED BY		7. UNIT AGREEMENT NAME
QIL GAS WELL Z C	OTHER	APR 1 2 1984	¥	Little Box Canyon Unit 8. FARM OR LEASE NAME
Yates Petroleum	Corporation	MIN 12 1304	13 (1)	Little Box Canyon Unit
3. ADDRESS OF OPERATOR		0. C. D. FERR		9. WELL NO.
207 South 4th St 4. LOCATION OF WELL (Report lo	., Artesia, NM 8	821 (ARTESIA, OFFICE	103.1	5
See also space 17 below.) At surface	ocation clearly and in accord	T21S-R22E	18	Undes. Box Canyon
800 FSL & 1	600 FWL, Sec. 7-3	121S-R22E	· Me co	11. SEC., T., R., M., OR BLK. AND SUBVEY OB AREA
		NEW	MEXIL	
14. PERMIT NO.	15. ELEVATIONS (S	Show whether DF, RT, GR, etc.)		Unit N, Sec. 7-T21S-R2 12. COUNTY OB PARISH 13. STATE
		4429' GR		Eddy NM
16. Ch	ieck Appropriate Box T	o Indicate Nature of Notic	e. Report, or Ot	her Data
	OF INTENTION TO :	1		NT REPORT OF:
TEST WATER SHUT-OFF	PULL OR ALTER CASE	NG WATER SH	UT-OFF X	REPAIRING WELL
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE	TREATMENT	ALTERING CASING
SHOOT OR ACIDIZE	ABANDON*		OR ACIDIZING	ABANDONMENT*
(Other)	CHANGE PLANS	(Other)(Nor	E: Report results o	f multiple completion on Well ion Report and Log form.)
17. DESCRIBE PROPOSED OR COMPL	ETED OPERATIONS (Clearly st	ate all pertinent details, and giv	e pertinent dates, in	ncluding estimated date of starting an depths for all markers and zones peri
anced with Really-ML	x. Began drillir	ng with rotary tools	5 5:00 PM 2-	3-84. Lost circulatio
115'. Sweep hole with a sacks Class C 2% Carbon C 2	ith mud and LCM. notched guide sh aCl2. Compressiv g to 1000 psi, re Ran Temperature 50 sacks Class C otted 125 sacks C d out 11:45 AM 2-	Ran 10 joints of 1 noe set 366'. Flapp re strength of cemer eleased presure and Survey and found to 4% CaCl2. PD 5:45 Class C 4% CaCl2. H 5-84. WOC 13 hrs a	13-3/8" 54.5 per float se nt - 1250 ps float held op of cement AM 2-5-84. PD 8:15 AM 2 and 45 min.	3-84. Lost circulation # J-55 ST&C casing set t 327'. Cemented w/ i in 12 hrs. PD 10:30 okay. Cement did not at 100'. Ran 1". Tagg WOC 2 hrs. Ran 1". -5-84. Cement circulat Nippled up and tested ug and resumed drilling
115'. Sweep hole with a sacks Class C 2% Carbon C 2	ith mud and LCM. notched guide sh aCl2. Compressiv g to 1000 psi, re Ran Temperature 50 sacks Class C otted 125 sacks C d out 11:45 AM 2-	Ran 10 joints of 1 noe set 366'. Flapp re strength of cemer eleased presure and Survey and found to 4% CaCl2. PD 5:45 Class C 4% CaCl2. H 5-84. WOC 13 hrs a	13-3/8" 54.5 per float se nt - 1250 ps float held op of cement AM 2-5-84. PD 8:15 AM 2 and 45 min.	<pre># J-55 ST&C casing set t 327'. Cemented w/ i in 12 hrs. PD 10:30 okay. Cement did not at 100'. Ran 1". Tagg WOC 2 hrs. Ran 1". -5-84. Cement circulat Nippled up and tested</pre>
115'. Sweep hole with a sacks Class C 2% Carbon C 2	ith mud and LCM. notched guide sh aCl2. Compressiv g to 1000 psi, re Ran Temperature 50 sacks Class C otted 125 sacks C d out 11:45 AM 2-	Ran 10 joints of 1 noe set 366'. Flapp re strength of cemer eleased presure and Survey and found to 4% CaCl2. PD 5:45 Class C 4% CaCl2. H 5-84. WOC 13 hrs a	13-3/8" 54.5 per float se nt - 1250 ps float held op of cement AM 2-5-84. PD 8:15 AM 2 and 45 min.	<pre># J-55 ST&C casing set t 327'. Cemented w/ i in 12 hrs. PD 10:30 okay. Cement did not at 100'. Ran 1". Tagg WOC 2 hrs. Ran 1". -5-84. Cement circulat Nippled up and tested</pre>
115'. Sweep hole with a sacks Class C 2% Carbon C 2	ith mud and LCM. notched guide sh aCl2. Compressiv g to 1000 psi, re Ran Temperature 50 sacks Class C otted 125 sacks C d out 11:45 AM 2-	Ran 10 joints of 1 noe set 366'. Flapp re strength of cemer eleased presure and Survey and found to 4% CaCl2. PD 5:45 Class C 4% CaCl2. H 5-84. WOC 13 hrs a	13-3/8" 54.5 per float se nt - 1250 ps float held op of cement AM 2-5-84. PD 8:15 AM 2 and 45 min.	<pre># J-55 ST&C casing set t 327'. Cemented w/ i in 12 hrs. PD 10:30 okay. Cement did not at 100'. Ran 1". Tagg WOC 2 hrs. Ran 1". -5-84. Cement circulat Nippled up and tested</pre>
115'. Sweep hole with a sacks Class C 2% Carbon C 2	ith mud and LCM. notched guide sh aCl2. Compressiv g to 1000 psi, re Ran Temperature 50 sacks Class C otted 125 sacks C d out 11:45 AM 2-	Ran 10 joints of 1 noe set 366'. Flapp re strength of cemer eleased presure and Survey and found to 4% CaCl2. PD 5:45 Class C 4% CaCl2. H 5-84. WOC 13 hrs a	13-3/8" 54.5 per float se nt - 1250 ps float held op of cement AM 2-5-84. PD 8:15 AM 2 and 45 min.	<pre># J-55 ST&C casing set t 327'. Cemented w/ i in 12 hrs. PD 10:30 okay. Cement did not at 100'. Ran 1". Tagg WOC 2 hrs. Ran 1". -5-84. Cement circulat Nippled up and tested</pre>
115'. Sweep hole wi '. 1-Texas Pattern sacks Class C 2% Ca 2-4-84. Bumped plug culate. WOC 6 hrs. ent 110'. Spotted 1 ged cement 40'. Spo acks. WOC. Drilled 1000 psi for 30 minu	ith mud and LCM. notched guide sh aCl2. Compressiv g to 1000 psi, re Ran Temperature 50 sacks Class C otted 125 sacks C d out 11:45 AM 2- utes, OK. Reduce	Ran 10 joints of 1 noe set 366'. Flapp re strength of cemer eleased presure and Survey and found to 4% CaCl2. PD 5:45 Class C 4% CaCl2. H 5-84. WOC 13 hrs a	13-3/8" 54.5 per float se nt - 1250 ps float held op of cement AM 2-5-84. PD 8:15 AM 2 and 45 min.	<pre># J-55 ST&C casing set t 327'. Cemented w/ i in 12 hrs. PD 10:30 okay. Cement did not at 100'. Ran 1". Tagg WOC 2 hrs. Ran 1". -5-84. Cement circulat Nippled up and tested</pre>
115'. Sweep hole wi '. 1-Texas Pattern sacks Class C 2% Ca 2-4-84. Bumped plug culate. WOC 6 hrs. ent 110'. Spotted 1 ged cement 40'. Spo acks. WOC. Drilled 1000 psi for 30 minu	ith mud and LCM. notched guide sh aCl2. Compressiv g to 1000 psi, re Ran Temperature 50 sacks Class C otted 125 sacks C d out 11:45 AM 2- utes, OK. Reduce	Ran 10 joints of 1 noe set 366'. Flapp re strength of cemen eleased presure and Survey and found to 4% CaCl2. PD 5:45 Class C 4% CaCl2. H 5-84. WOC 13 hrs a red hole to 12-1/4".	13-3/8" 54.5 ber float se at - 1250 ps float held op of cement AM 2-5-84. 2D 8:15 AM 2 and 45 min. Drilled pl	# J-55 ST&C casing set t 327'. Cemented w/ i in 12 hrs. PD 10:30 okay. Cement did not at 100'. Ran 1". Tagg WOC 2 hrs. Ran 1". -5-84. Cement circulat Nippled up and tested ug and resumed drilling
115'. Sweep hole wi '. 1-Texas Pattern sacks Class C 2% Ca 2-4-84. Bumped plug culate. WOC 6 hrs. ent 110'. Spotted 1 ged cement 40'. Spo acks. WOC. Drilled 1000 psi for 30 minu 18. I hereby certify that the for SIGNER Control	ith mud and LCM. notched guide sh aC12. Compressiv g to 1000 psi, re Ran Temperature 50 sacks Class C otted 125 sacks C d out 11:45 AM 2- utes, OK. Reduce	Ran 10 joints of 1 noe set 366'. Flapp re strength of cemer eleased presure and Survey and found to 4% CaCl2. PD 5:45 Class C 4% CaCl2. H 5-84. WOC 13 hrs a	13-3/8" 54.5 ber float se at - 1250 ps float held op of cement AM 2-5-84. 2D 8:15 AM 2 and 45 min. Drilled pl	<pre># J-55 ST&C casing set t 327'. Cemented w/ i in 12 hrs. PD 10:30 okay. Cement did not at 100'. Ran 1". Tagg WOC 2 hrs. Ran 1". -5-84. Cement circulat Nippled up and tested</pre>
115'. Sweep hole with interval in the second sec	ith mud and LCM. notched guide sh aC12. Compressiv g to 1000 psi, re Ran Temperature 50 sacks Class C otted 125 sacks C d out 11:45 AM 2- utes, OK. Reduce utes, OK. Reduce	Ran 10 joints of 1 noe set 366'. Flapp re strength of cemer eleased presure and Survey and found to 4% CaCl2. PD 5:45 Class C 4% CaCl2. H 5-84. WOC 13 hrs a red hole to 12-1/4".	13-3/8" 54.5 ber float se at - 1250 ps float held op of cement AM 2-5-84. 2D 8:15 AM 2 and 45 min. Drilled pl	# J-55 ST&C casing set t 327'. Cemented w/ i in 12 hrs. PD 10:30 okay. Cement did not at 100'. Ran 1". Tagg WOC 2 hrs. Ran 1". -5-84. Cement circular Nippled up and tested ug and resumed drilling
115'. Sweep hole wi '. 1-Texas Pattern sacks Class C 2% Ca 2-4-84. Bumped plug culate. WOC 6 hrs. ent 110'. Spotted 1 ged cement 40'. Spo acks. WOC. Drilled 1000 psi for 30 minu 18. I hereby certify that the for SIGNET Control	ith mud and LCM. notched guide sh aC12. Compressiv g to 1000 psi, re Ran Temperature 50 sacks Class C otted 125 sacks C d out 11:45 AM 2- utes, OK. Reduce utes, OK. Reduce	Ran 10 joints of 1 noe set 366'. Flapp re strength of cemen eleased presure and Survey and found to 4% CaCl2. PD 5:45 Class C 4% CaCl2. H 5-84. WOC 13 hrs a red hole to 12-1/4".	13-3/8" 54.5 ber float se at - 1250 ps float held op of cement AM 2-5-84. 2D 8:15 AM 2 and 45 min. Drilled pl	# J-55 ST&C casing set t 327'. Cemented w/ i in 12 hrs. PD 10:30 okay. Cement did not at 100'. Ran 1". Tagg WOC 2 hrs. Ran 1". -5-84. Cement circulat Nippled up and tested ug and resumed drilling
115'. Sweep hole with interval in the second sec	ith mud and LCM. notched guide sh aC12. Compressiv g to 1000 psi, re Ran Temperature 50 sacks Class C otted 125 sacks C d out 11:45 AM 2- utes, OK. Reduce utes, OK. Reduce	Ran 10 joints of 1 noe set 366'. Flapp re strength of cemer eleased presure and Survey and found to 4% CaCl2. PD 5:45 Class C 4% CaCl2. H 5-84. WOC 13 hrs a red hole to 12-1/4".	13-3/8" 54.5 ber float se at - 1250 ps float held op of cement AM 2-5-84. 2D 8:15 AM 2 and 45 min. Drilled pl	# J-55 ST&C casing set t 327'. Cemented w/ i in 12 hrs. PD 10:30 okay. Cement did not at 100'. Ran 1". Tagg WOC 2 hrs. Ran 1". -5-84. Cement circular Nippled up and tested ug and resumed drilling
115'. Sweep hole with interval in the second sec	ith mud and LCM. notched guide sh aCl2. Compressiv g to 1000 psi, re Ran Temperature 50 sacks Class C otted 125 sacks C d out 11:45 AM 2- utes, OK. Reduce the office of the sacks Compared to the sacks of the sacks	Ran 10 joints of 1 noe set 366'. Flapp re strength of cemer eleased presure and Survey and found to 4% CaCl2. PD 5:45 Class C 4% CaCl2. H 5-84. WOC 13 hrs a red hole to 12-1/4".	13-3/8" 54.5 per float se ht - 1250 ps float held op of cement AM 2-5-84. 20 8:15 AM 2 and 45 min. Drilled pl pervisor	# J-55 ST&C casing set t 327'. Cemented w/ i in 12 hrs. PD 10:30 okay. Cement did not at 100'. Ran 1". Tagg WOC 2 hrs. Ran 1". -5-84. Cement circular Nippled up and tested ug and resumed drilling