

C/S

Form 9-331  
(May 1963)

NM OIL CONS. CO. SSION

Drawer DD

SUBMIT IN TRIPLICATE.  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

UNITED STATES  
DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

ARTESIA, OFFICE

5. LEASE DESIGNATION AND SERIAL NO.

NM 12241

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Little Box Canyon Unit

8. FARM OR LEASE NAME

Little Box Canyon Unit

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

Undes. Box Canyon

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unit N, Sec. 7-T21S-R22E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4429' GR

12. COUNTY OR PARISH

Eddy

13. STATE

NM

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Intermediate Casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Ran 45 jts of 9-5/8" 36# K-55 ST&C casing set 1800'. 1-Texas Pattern notched guide shoe set 1800'. Flapper float set 1760'. Cemented w/500 sacks Class C Pacesetter Lite, 2% CaCl2. Tailed in w/250 sacks Class C 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hrs. PD 5:20 AM 2-8-84. Bumped plug to 1000 psi, released pressure and float held okay. Cement did not circulate. WOC 6 hrs. Ran Temperature Survey and found top of cement 840'. Ran 1". Tagged cement 860'. Spotted 50 sacks Class C Neat, 2% CaCl2. PD 1:50 PM 2-8-84. WOC 2 hrs. Ran 1". Tagged cement 840'. Spotted 100 sacks Class C Neat 2% CaCl2. PD 4:05 PM 2-8-84. WOC 2 hrs and 30 minutes. Ran 1". Tagged cement 840'. Spotted 25 sacks Class C Neat 4% CaCl2. PD 7:10 PM 2-8-84. WOC 45 minutes. Ran 1". Tagged cement 780'. Spotted 50 sacks Class C Neat 4% CaCl2. PD 8:15 PM 2-8-84. WOC 1 hour and 30 minutes. Ran 1". Tagged cement 580'. Spotted 75 sacks Class C Neat 4% CaCl2. PD 10:15 PM 2-8-84. WOC 3 hrs. Ran 1". Tagged cement 540'. Spotted 50 sacks Class C Neat 4% CaCl2. PD 1:40 AM 2-9-84. WOC 2 hrs. Ran 1". Tagged cement 430". Spotted 50 sacks Class C Neat 4% CaCl2. PD 4:05 AM 2-9-84. WOC 2 hrs and 25 minutes. Ran 1". Tagged cement 403'. Spotted 50 sacks Class C Neat 4% CaCl2. PD 6:50 AM 2-9-84. WOC 3 hrs. Ran 1". Tagged cement 217'. Spotted 175 sacks Class C Neat 4% CaCl2. PD 10:20 AM 2-9-84. Cement circulated 5 sacks. WOC. Note: BLM witnessed. Drilled out 9:30 AM 2-10-84. WOC 52 hrs and 10 minutes. NU and tested to 1000 psi for 30 minutes, OK. Reduced hole to 8-3/4". Drilled plug and resumed drilling.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Production Supervisor

DATE 2-13-84

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL MAY 1 1984

Carlsbad

NEW MEXICO

\*See Instructions on Reverse Side