

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

2-28-84

Operator <u>YPC</u>		Lease <u>S. AVALON VI</u>		Well # <u>1</u>	
Location of Well	Unit <u>K</u>	Section <u>23</u>	Township <u>21</u>	Range <u>26</u>	County <u>EDDY</u>
Drilling Contractor	<u>N/A</u>		Type of Equipment <u>ROTARY</u>		

* Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17 1/2	13 3/8	48 #	NEW	610	CIRC
* 12 1/4	9 5/8	32 #	"	2720 2500	CIRC
7 7/8	4 1/2 or 5 1/2	11.6, 13, 17, or 20	"	TD	600 SX.

Casing Data:

Surface 56 joints of 9 5/8 inch 32 # Grade J-55
(Approved) (Rejected)

Inspected by BW Weaver date 2-28-84

Cementing Program

Size of hole 12 1/4 Size of Casing 9 5/8 Sacks cement required 250

Type of Shoe used Tex. Air Float collar used Insert Btm 3 jts welded Yes

TD of hole 2221 Set 2223 Feet of 9 5/8 Inch 32 # Grade J-55

New-used csg. @ 2223 with 250 sacks neat cement around shoe

+ 800 sax Pace Setter etc additives 1% CC

Plug down @ 7:00 (AM) (PM) Date 2-28-84

Cement circulated yes No. of Sacks 115

Cemented by Western Witnessed by BW Weaver

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: Loss Zone @ 1366