

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-015-24769

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

South Avalon YI Com

8. Well No.

1

9. Pool name or Wildcat

NE Happy Valley Strawn

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South Fourth Street - Artesia, NM 88210

4. Well Location

Unit Letter K : 1980 Feet From The South

Line and 00

Feet From The West

Line

Section 23

Township 21S

Range 26E

NMPM Eddy

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3140' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: Add Strawn Sand pay ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Propose to add Strawn Sand pay and commingle with Strawn Lime as follows:

1. Nipple down tree and nipple up BOP. Drop standing valve and test tubing to 2500 psi. Retrieve standing valve, circulate gas out of hole and reset packer at 9700'±. Test annulus to 1000 psi.
2. Swab well dry. Perforate 9823-9829' (Strawn Sand) with 1-11/16" Enerjet gun (4 SPF).
3. Test well.
4. If decision made to acidize, will acidize perforations 9823-9829' w/1000 gallons 7-1/2% HCL Morrow type acid containing 1000 scf/bbl nitrogen with ball sealers. Flush acid with 2% KCL water containing 1000 scf/bbl nitrogen.
5. Swab/flow test Strawn Sand. When testing complete, move tools and place entire Strawn interval 9823-9953' on production.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Rusty Klein

TITLE

Production Clerk

DATE

9-8-94

TYPE OR PRINT NAME

Rusty Klein

505-748-1471
TELEPHONE NO.

(This space for State Use)

SUPERVISOR, DISTRICT II

SEP 19 1994

APPROVED BY

TITLE

DATE