STATE OF NEW MEXICO			
ENERGY AND MINERALS DEPARTME			
NB. BF COPIER BLEETVER	OIL CONSERVATION DIVISION		
DISTRIBUTION	P. O. BOX 2088		Form C-103
SANTA FE	SANTA FE, NEW MEX	ICO 87501	Revised 10-1-78
FILE			5a. Indicate Type of Lease
U.S.G.S.			
LAND OFFICE			State X Fee
OPERATOR	J		5. State Oil & Gas Lease No. K-6261
(DO NOT USE THIS FORM FOR PRO	Y NOTICES AND REPORTS ON WELL POSALS 10 DRILL ON TO DEEPEN OR PLUG RACK TO A 100 FOR PERMIT IFORM C-101) FOR SUCH PROPOS	RECEIVED BY	
I. OIL X GAB WELL	OTHER-	APR 03 1984	7 Unit Agreement Name
2. Name of Operator		O. C. D.	8 Farm or Lease Name
Yates Petroleum Con	poration V	ARTESIA, OFFICE	Citdel ZG State
3. Address of Operator	· · · · · · · · · · · · · · · · · · ·		9. Well No.
207 South 4th St.,	Artesia, NM 88210		1
4. Location of Well			10. Field and Pool, or Wildcat
UNIT LETTER A 3	0 FEET FROM THE North LINE	AND SO FEET FROM	Undes. Delaware
THE East LINE, SECTION	DN 36 TOWNSHIP 205 R	<u> </u>	
	15. Elevation (Show whether DF, RT,	GR, etc.)	12. County
	3289' GR		Eddy
16. Check	Appropriate Box To Indicate Nature	of Notice. Report of Oth	
	ITENTION TO:		REPORT OF:
PERFORM REMEDIAL WORK			ALTERING CASING
FULL CR ALTER CASING		TEST AND CEMENT JOB	PLUG AND ABANDONMENT
OTHER	нто	ER	

tinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 17-1/2" hole 3:00 PM 3-11-84. Lost circulation at 109'. Pumped 100 bbl pill. Regained 75% returns. Lost circulation at 115'. Dry drilled. Ran 10 jts of 13-3/8" 54.5# J-55 ST&C casing set at 408'. 1-Texas Pattern guide shoe set 408'. Insert float set 355'. Cemented w/325 sacks Class "C" 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hrs. PD 8:15 AM 3-12-84. Bumped plug to 1000 psi, released pressure and float held okay. Cement did not circulate. WOC 6 hrs. Ran Temperature Survey and found top of cement at 90'. Ready-Mix to surface w/2 yards. WOC. Drilled out 8:15 PM 3-12-84. WOC 12 hrs. Cut off and welded on flow nipple Tested casing to 1000 psi for 30 minutes, OK. Reduced hole to 12-1/4". Drilled plug and resumed drilling. Ran 59 jts of 8-5/8" 24# K-55 ST&C casing set 2390'. 1-Texas Pattern notched guide shoe set 2390'. Insert float set 2350'. Cemented w/ 550 sacks Howco Lite, 10#/sx gilsonite, 1/4#/sx flocele 3% CaCl2. Tailed in w/250 sacks Class "C" 2% CaCl2. Compresive strength of cement - 1250 psi in 12 hrs. PD 2:15 AM 3-18-84. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 30 sacks. WOC. Drilled out 8:15 PM 3-17-84. WOC 18 hrs. NU and tested to 1000 psi for 30 minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

CITDEL "ZG" WELL NAME CORRECTED FROM: TO:

Post 28-3 4-6-84 chy. Well home CITDEL "ZG" STATE 8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

inner ju anda Doo deur	Production Supervisor	DATE 4-2-84
	Original Signed By Leslie A. Clements TITLE <u>Supervisor District II</u>	APR 0 3 1984

ONDITIONS OF APPROVAL, IF ANY: