Drawer DD
Artesia, NM 88210

9/SF

Form 9-330
(Rev. 5-63)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE* (See other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R355.5.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

RECEIVED
AUG 03 1984
O. C. D.
ARTESIA, OFFICE

5. LEASE DESIGNATION AND SERIAL NO.: NM-40256

6. IF INDIAN, ALLOTTEE OR TRIBE NAME: --

7. UNIT AGREEMENT NAME: --

8. FARM OR LEASE NAME: Stott Federal

9. WELL NO.: 2

10. FIELD AND POOL, OR WILDCAT: Undesig. - Bone Spring

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA: 1-21S-27E

1a. TYPE OF WELL: OIL WELL [X] GAS WELL [ ] DR [ ] Other

b. TYPE OF COMPLETION: NEW WELL [X] WORK OVER [ ] DEEP-EN [ ] PLUG BACK [ ] DIFF. RESVR. [ ] Other

2. NAME OF OPERATOR: Exxon Corporation

3. ADDRESS OF OPERATOR: P. O. Box 1600, Midland, TX 79702

4. LOCATION OF WELL (*Report location clearly and in accordance with any State requirements*)*
At surface: 1980' FWL & 1392.3' FNL of Sec. 1 (SE/NW)
At top prod. interval reported below
At total depth

14. PERMIT NO.	DATE ISSUED	12. COUNTY OR PARISH	13. STATE
	4-13-84	Eddy	New Mexico

15. DATE SPUDDED	16. DATE T.D. REACHED	17. DATE COMPL. (*Ready to prod.*)	18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*	19. ELEV. CASINGHEAD
6-17-84	7-10-84	7-21-84	3197' GR	

20. TOTAL DEPTH, MD & TVD	21. PLUG, BACK T.D., MD & TVD	22. IF MULTIPLE COMPL., HOW MANY*	23. INTERVALS DRILLED BY	ROTARY TOOLS	CABLE TOOLS
5670			→	0 - 5670'	

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*: 5537 - 5560' Bone Spring

25. WAS DIRECTIONAL SURVEY MADE: No

26. TYPE ELECTRIC AND OTHER LOGS RUN: FDC-CNL; DLL-MSFL; Sidewall Cores

27. WAS WELL CORED: No

28. CASING RECORD (*Report all strings set in well*)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
13-3/8"	48#	575'	17-1/2"	600 sx C1C	
8-5/8"	24#	2495'	11"	2000 sx Pacesetter Lite; 400 sx C1C	
				700 sx C1C Neat	
5-1/2"	14, 15.5	5661'	7-7/8"	1215 sx C1C	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)

30. TUBING RECORD

SIZE	DEPTH SET (MD)	PACKER SET (MD)
2-7/8"	5300	5300

31. PERFORATION RECORD (*Interval, size and number*)
Perf 5537 - 5560 w/ 96 shots

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
5537 - 5560	2500 gals 15% HCl
	20,000 gals YFCO_2, 28,700#
	20-40 mesh sand

33.* PRODUCTION

DATE FIRST PRODUCTION	PRODUCTION METHOD (*Flowing, gas lift, pumping—size and type of pump*)	WELL STATUS (*Producing or shut-in*)
7-19-84	Flowing	Producing

DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD →	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
7-22-84	24	20/64"		111	318	0	2865

FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE →	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)
215						45

34. DISPOSITION OF GAS (*Sold, used for fuel, vented, etc.*): Flared

TEST WITNESSED BY:

ACCEPTED FOR RECORD
AUG 21 1984

35. LIST OF ATTACHMENTS

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED [signature] TITLE Unit Head Carlsbad, NEW MEXICO DATE 7-25-84

*(See Instructions and Spaces for Additional Data on Reverse Side)

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.
If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.
Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.
Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.
Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.
Item 29: *"Sacks Cement":* Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.
Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES:
SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.
Bone Spring	5402		limestone, shale

38. GEOLOGIC MARKERS

NAME	TOP	
	MEAS. DEPTH	TRUE VERT. DEPTH
Delaware Sand	2804	
Bone Spring	5402	

U.S. GOVERNMENT PRINTING OFFICE: 1963—O-683636