

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

FORM APPROVED
Budget Bureau No. 1004-0135
Expires September 30, 1990

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

RECEIVED

Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

OCT 15 '90

Name of Operator

HONDO OIL & GAS COMPANY

C. C. D.
OFFICE

Address and Telephone No.

P. O. BOX 2208, ROSWELL, NM 88202 (505)625-6745

Location of Well (Footage, Sec., T., R., M., or Survey Description)

3009' FNL & 660' FWL; Sec. 6-T21S-R2/E

7. If Unit or CA. Agreement Designation

8. Well Name and No.

KURLAND "A" #1

9. API Well No.

3001524847

10. Field and Pool, or Exploratory Area

Avalon Bone Springs

11. County or Parish, State

Eddy Co., NM

2. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection

Perforating & Acidizing

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

09/11/90 Tagged @ 4972', prep to perf and acidize Bone Springs.

09/12/90 RU Wedge Wireline perforate 4614', 4615', 4622', 4624', 4652', 4653', 4695', 4696', 4697', 4698', 4699', 4722', 4723', 4724', 4725', 4726', 4727', 4840', 4857', 4877', 4878', 4013', 4014', 4015', 4017', 4018', 4019' (27 shots) 1 SPF. RIH w/ 5 1/2" - 15.5#, Model R pkr - set @ 4768'. Pump 4000 gals 30% pad acid & 50 ball sealers. Acid job - rate 3 - 3.9 BPM, press. 2300 to 2660 psi good break to 1570 psi, good ball action, ISIP 900 psi. Swab well back. POH w/ pkr.

09/13/90 Acidize (4695'-4727') 11 holes 3000 gals 30% pad acid. Set pkr @ 4580', acidized (4614'-4727') with 4000 gals 30% pad acid.

09/16/90 RIH w/ 2 7/8" tbg, SN @ 4957', PBTD 4984'.

14. I hereby certify that the foregoing is true and correct

Signed [Signature]

Title Petroleum Engineer

Date 10/10/90

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statement or representations as to any matter within its jurisdiction.