

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER 10  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

10-2-84

Operator <u>Mesa Pet. Co.</u>		Lease <u>Saladar St.</u>		Well # <u>1</u>	
Location of Well	Unit <u>K</u>	Section <u>24</u>	Township <u>20 S</u>	Range <u>27 E</u>	County <u>EDDY</u>
Drilling Contractor	<u>N/A</u>		Type of Equipment <u>ROTARY</u>		

\* Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2</u>	<u>13 3/8</u>	<u>48</u>	<u>NEW</u>	<u>600</u>	<u>CIRC</u>
<u>* 12"</u>	<u>8 5/8</u>	<u>24</u>	<u>"</u>	<u>2500</u>	<u>CIRC</u>
<u>7 7/8"</u>	<u>5 1/2</u>	<u>14</u>	<u>"</u>	<u>3200</u>	<u>550 SxS.</u>

Casing Data:

Surface 62 joints of 8 5/8 inch 24 # Grade J-55

yes

(Approved) (Rejected)

Inspected by BW Weaver date 5-21-84

Cementing Program

Size of hole 12 1/4 Size of Casing 8 5/8 Sacks cement required 150

Type of Shoe used Guide Float collar used collar Btm 3 jts welded yes

TD of hole 2515 Set 2528 Feet of 8 5/8 Inch 24 # Grade J-55

New ~~used~~ csg. @ 2528 with 150 sacks neat cement around shoe

+ 1000 sax BJ lite additives

Plug down @ 5:30 (AM) (PM) Date 5-21-84

Cement circulated yes No. of Sacks 200

Cemented by BJ Hughes Witnessed by BW Weaver

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: last Drilling Break @ 2275