

Antonia, NM 88310

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Form Approved  
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR  
The Superior Oil Company

3. ADDRESS OF OPERATOR  
P.O. Box 3901, Midland, TX 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1554' FNL, 1980' FEL of Section 1

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other)	Spud & 13-3/8" Casing.	

5. LEASE  
NM-17095

6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
O. C. D.

7. UNIT AGREEMENT NAME  
ARTESIA, OFFICE

8. FARM OR LEASE NAME  
Government "D"

9. WELL NO.  
4

10. FIELD OR WILDCAT NAME  
~~Wildcat~~ - Bone Spring

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Section 1, T21S, R27E

12. COUNTY OR PARISH  
Eddy

13. STATE  
NM

14. API NO.  
3196' GR

15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. Spudded @ 1300 hrs on 8-7-84.
2. Ran 16 jts 13-3/8" 54.5# K-55 ST&C csg. set @ 655'.
3. Cmt'd w/700 sx Class C + 2% C12. Bumped plug 2/800 PSI - held O.K.
4. Cement set 35.75 hrs prior to drilling out.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED G. F. Tate TITLE Division Opr. Supt DATE 8-24-84

ACCEPTED FOR RECORD (Leave space for Federal or State office use)

APPROVED BY G. F. Tate TITLE Division Opr. Supt DATE 8-24-84

CONDITIONS OF APPROVAL, IF ANY:  
AUG 30 1984

Carlsbad, NEW MEXICO \*See Instructions on Reverse Side