

9/5F

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
well well

2. NAME OF OPERATOR
The Superior Oil Company

3. ADDRESS OF OPERATOR
P.O. Box 3901, Midland, Texas 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1554' FNL, 1980' FEL of Section 1
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) 8-5/8" Casing Detail	

5. LEASE
NM-17095

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME RECEIVED BY

8. FARM OR LEASE NAME AUG 31 1984
Government "D"

9. WELL NO. O. C. D.
4 ARTESIA, OFFICE

10. FIELD OR WILDCAT NAME Wildcat Bone Spring

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Section 1, T21S, R27E

12. COUNTY OR PARISH Eddy 13. STATE NM

14. API NO.
3196' GR

15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Ran 58 jts 8-5/8" 54# K-55 ST&C csg, set @ 2437' w/DV tool @ 1717'
2. Cmdt 1-25 stage w/150 sx Lite + 1/4#/sx Cello-Seal + 3#/sx Hj-Seal. Followed w/300 sx Class C + 2% Ca Cl2.
3. Cmdt 2-nd stage w/550 sx Lite + 1/4 #/sx Cello-Seal, 1000 sx Lite. Followed w/100 sx Class C. TOC @ 675.

WOC in excess of 14 hrs.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED G. E. Tate TITLE Division Opr. Supt. DATE 8-24-84

ACCEPTED FOR RECORD (This space for Federal or State office use)

APPROVED BY GEO TITLE DATE

CONDITIONS OF APPROVAL IF ANY:

AUG 30 1984

Carlsbad

NEW MEXICO *See Instructions on Reverse Side