

MEASURED DEPTH FEET	DRIFT ANGLE D M	DRIFT DIRECTION D	COURSE LENGTH FEET	TRUE VERTICAL DEPTH FEET	RED TANGULAR CORR IN A T E S FEET	DOGLEG SEVERITY DG/100FT
6300.	0 45	N 23 W	100.	6298.03	25.90 S	0.34
6400.	0 45	N 45 W	100.	6398.02	24.82 S	0.29
6500.	0 45	N 70 W	100.	6498.01	24.12 S	0.32
6600.	0 45	N 85 W	100.	6598.00	23.84 S	0.20
6700.	0 45	S 52 W	100.	6697.99	24.20 S	0.55
6800.	0 45	S 46 W	100.	6797.98	25.06 S	0.08
6900.	0 15	S 20 W	100.	6897.98	25.79 S	0.54
7000.	0 30	S 70 W	100.	6997.98	26.24 S	0.39
7100.	0 30	S 85 W	100.	7097.97	26.43 S	0.13
7200.	0 45	S 22 W	100.	7197.97	27.04 S	0.69
7300.	1 15	S 38 W	100.	7297.95	28.55 S	0.57
7400.	1 0	S 40 W	100.	7397.93	30.08 S	0.25
7500.	0 45	S 5 E	100.	7497.92	31.43 S	0.71
7600.	0 45	S 20 E	100.	7597.91	32.71 S	0.20
7700.	1 15	S 3 W	100.	7697.90	34.48 S	0.63
7800.	1 45	S 4 W	100.	7797.86	37.09 S	0.50
7900.	1 45	S 4 E	100.	7897.81	40.15 S	0.24
8000.	2 15	S 5 E	100.	7997.75	43.63 S	0.50
8100.	2 30	S 26 E	100.	8097.67	47.60 S	0.90
8200.	2 15	S 16 E	100.	8197.58	51.46 S	0.43
8300.	2 0	S 25 E	100.	8297.51	54.93 S	0.42
8400.	2 15	S 5 E	100.	8397.45	58.49 S	0.78
8500.	3 15	S 10 E	100.	8497.33	63.24 S	1.03
8600.	3 45	S 14 E	100.	8597.14	69.21 S	0.56
8700.	4 0	S 6 E	100.	8696.91	75.86 S	0.59
8800.	4 0	S 4 W	100.	8796.67	82.83 S	0.70
8900.	4 0	S 1 W	100.	8896.43	89.80 S	0.21
9000.	3 30	S 0 E	100.	8996.21	96.34 S	0.50
9100.	3 0	S 5 E	100.	9096.05	102.00 S	0.57
9200.	2 15	S 0 E	100.	9195.95	106.57 S	0.78