

TIME DATE

06:14:07 17-SEP-84

MEASURED DEPTH FEET	DRIFT ANGLE D M	DRIFT DIRECTION D	COURSE LENGTH FEET	TRUE VERTICAL DEPTH FEET	RECTOR C O O R D I N A T E S FEET	ANGULAR S E V E R I T Y DG/100FT
1500.	1 0	S 46 W	50.	1499.61	5.20 S	29.42 W
1550.	1 0	S 28 W	50.	1549.61	5.89 S	29.94 W
1600.	1 0	S 27 W	50.	1599.60	6.67 S	30.34 W
1650.	1 15	S 22 W	50.	1649.59	7.56 S	30.75 W
1700.	1 15	S 28 W	50.	1699.58	8.55 S	31.21 W
1750.	1 15	S 32 W	50.	1749.56	9.49 S	31.75 W
1800.	1 30	S 30 W	50.	1799.55	10.52 S	32.37 W
1850.	1 15	S 25 W	50.	1849.54	11.58 S	32.93 W
1900.	1 15	S 28 W	50.	1899.52	12.56 S	33.41 W
1950.	1 30	S 27 W	50.	1949.51	13.62 S	33.97 W
2000.	1 30	S 35 W	50.	1999.49	14.74 S	34.64 W
2050.	1 30	S 35 W	50.	2049.48	15.75 S	35.48 W
2100.	1 30	S 54 W	50.	2099.46	16.60 S	36.47 W
2150.	1 30	S 58 W	50.	2149.44	17.31 S	37.56 W
2200.	2 15	S 68 W	50.	2199.41	18.07 S	39.01 W
2250.	2 30	S 82 W	50.	2249.37	18.60 S	41.01 W
2300.	2 45	S 75 W	50.	2299.32	19.06 S	43.25 W
2350.	3 0	S 73 W	50.	2349.26	19.75 S	45.66 W
2400.	2 30	S 71 W	50.	2399.20	20.49 S	47.95 W
2450.	2 15	S 72 W	50.	2449.16	21.15 S	49.91 W
2500.	2 0	S 84 W	50.	2499.12	21.53 S	51.72 W
2550.	2 15	S 83 W	50.	2549.09	21.74 S	53.56 W
2600.	2 0	S 73 W	50.	2599.05	22.13 S	55.37 W
2640.	1 45	S 74 W	40.	2639.03	22.50 S	56.63 W
2700.	1 30	S 76 W	60.	2699.01	22.94 S	58.27 W
2800.	2 0	S 74 W	100.	2798.96	23.73 S	61.22 W
2900.	1 45	S 79 W	100.	2898.91	24.50 S	64.40 W
3000.	1 45	S 79 W	100.	2998.86	25.08 S	67.40 W
3100.	2 0	N 88 W	100.	3098.81	25.34 S	70.66 W
3200.	2 15	N 90 W	100.	3198.74	25.27 S	74.37 W

RECEIVED

OCT 24 1984

CLERK
HOBBS DEPT.