

OIL CONSERVATION DIVISION

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	<input checked="" type="checkbox"/>
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

RECEIVED BY  
FEB 28 1985  
O. C. D.  
ARTESIA OFFICE

5a. Indicate Type of Lease  
State ☐ Fee ☒  
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
Name of Operator <i>Mahel Prod. Co. &amp; H. M. Inc.</i> <del>Superior Oil Company, The</del>	8. Farm or Lease Name <b>Burton Flat</b>
Address of Operator P.O. Box 3901, Midland, Texas 79702	9. Well No. <b>2</b>
Location of Well UNIT LETTER <b>0</b> . <b>3300</b> FEET FROM THE <b>South</b> LINE AND <b>1980</b> FEET FROM THE <b>East</b> LINE, SECTION <b>1</b> TOWNSHIP <b>21-S</b> RANGE <b>27-E</b> NMPM.	10. Field and Pool, or Wildcat <b>E. Avalon-Bone Spring</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>3178' GR</b>	12. County <b>Eddy</b>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

CORRECTED REPORT  
Spud and 13-3/8" Casing Detail

Spudded at 2400 hrs. on 11-29-84  
Ran 13-3/8", 54.5#, K-55, ST&C casing to 630' w/12 centralizers,  
Cemented with 675 sx Class "C" cement with 2% CACL.  
Displaced cement with 92 bbls. fresh water and circulated cement to surface.  
Bumped plug and cement job completed at 1:45 P.M., 12-1-84. Held 400 psi  
on plug for 3 1/2 hours with no pressure loss. Ran 11" bit and tagged  
top of cement inside 13-3/8" casing at 578'.  
Drilled out of shoe after W.O.C. 24+ hours.  
Drilling 11" hole.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. C. McConnell TITLE Environmental Specialist DATE 2-26-85  
W. C. McConnell Phone 915 688-1770  
APPROVED BY \_\_\_\_\_ TITLE Original Signed By  
Leslie A. Clements DATE FEB 28 1985  
Supervisor District II