

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Exp. 2-22-85

Operator <u>Y.P.C</u>		Lease <u>Anthill AAK ST</u>		Well # <u>1</u>	
Location of Well	Unit <u>0</u>	Section <u>2</u>	Township <u>20S</u>	Range <u>29E</u>	County <u>Eddy</u>
Drilling Contractor	<u>Sharp # 36</u>		Type of Equipment <u>ROTARY</u>		

* = CSG. TO WITNESS

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cemen
<u>17 1/2</u>	<u>13 3/8</u>	<u>48 #</u>	<u>NEW</u>	<u>600</u>	<u>CIRC</u>
* <u>12 1/4</u>	<u>9 5/8 7 7/8</u>	<u>36 #</u>	<u>"</u>	<u>2500</u>	<u>CIRC</u>
<u>7 7/8</u>	<u>5 1/2</u>	<u>17 #</u>	<u>"</u>	<u>TD</u>	<u>500 SX</u>

Casing Data:

Surface joints of 7 7/8 inch 26.40 # Grade K-55
Yes (Approved) (Rejected)

Inspected by BW Weaver date 9-28-84

Cementing Program

Size of hole 12 1/4 Size of Casing 7 7/8 Sacks cement required 300

Type of Shoe used Guide Float collar used Insert Btm 3 jts welded Yes

TD of hole 2662 Set 2662 Feet of 7 7/8 Inch 26 # Grade J-55

New-used csg. @ 2662 with 300 sacks neat cement around shoe

+ 800 SX sax Poc 6th 1/2 additives

Plug down @ 6:00 (AM) (PM) Date 9-29-84

Cement circulated No No. of Sacks

Cemented by Western Witnessed by BW Weaver

Temp. Survey ran @ 1:00 (AM) (PM) Date 9-30-84 top cement @ 1100

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: Ran 1145 7 7/8 Flush Joint Casing
Ran 1731 FT 9 5/8 #36 J-55 Casing Cut and Pulled 1585 FT Ran
1145 7 7/8 Flush Joint to 2662 FT

Ran 1" to 1107 Ran 200 SX @ 2% CC

Tag @ 825 Ran 600 SX @ 2% CC

Tag @ 780 Ran 100 SX @ 2% CC

Tag @ 780 Ran 200 SX @ 2% CC

Tag @ 780 Ran 600 SX @ 2% CC

Tag @ 552 Ran 250 SX @ 2% CC Cene Cement to Surface