

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radioactivity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn 10606	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka 10854	T. Pictured Cliffs	T. Penn. "D"
T. Yates	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres	T. Simpson	T. Gallup	T. Ignacio Qtzite
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinobry	T. Gr. Wash	T. Morrison	T.
T. Tubb	T. Granite	T. Todilto	T.
T. Drinkard	T. Delaware Shale 3522	T. Entrada	T.
T. Abo	T. Bone Springs 5912	T. Wingate	T.
T. Wolfcamp 9554	T. 3rd B.S. Sd 8960	T. Chinle	T.
T. Penn.	T. Morrow Clastic 11610	T. Permian	T.
T. Cisco (Bough C)	T. Lower Morrow 11905	T. Penn. "A"	T.
	Chester 12062		

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....	feet.
No. 2, from.....to.....	feet.
No. 3, from.....to.....	feet.
No. 4, from.....to.....	feet.

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	70	70	Surface, Rock	9040	9540	500	Sand, Shale, Lime, Dolo.
70	700	630	Redbeds, Anhydrite	9540	11600	2060	Lime, Shale
700	800	100	Anhy, Dolo, Shale, Sand	11600	12150	550	Sand, Shale, Lime
800	1410	610	Dolo, Anhy, Shale				
1410	1710	300	Anhy, Dolo, Sand				
1710	2060	350	Dolomite, Anhydrite				
2060	2620	560	Dolo, Anhy, Lime				
2620	3000	380	Dolomite, Anhydrite				
3000	3510	510	Dolomite				
3510	5900	2390	Dolomite, Sand, Shale				
5900	6170	270	Lime, Anhy, Shale, Sand				
6170	7220	1050	Lime, Shale				
7220	7450	230	Sand, Lime, Shale				
7450	7840	390	Lime, Shale				
7840	8330	490	Lime, Dolo, Shale, Sand				
8330	9040	710	Lime, Shale, Dolomite				