

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

RECEIVED BY

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
Perry R. Bass
3. ADDRESS OF OPERATOR
P. O. Box 2760, Midland, Tx 79702
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL & 660' FWL unit letter E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE
LC-067144
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Indian Flats Bass Federal
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
Indian Flats (Delaware)
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 35, T21S, R28E
12. COUNTY OR PARISH
Eddy
13. STATE
New Mexico
14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3170.4' GL

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

- | | | |
|-------------------------------------|--------------------------|--------------------------|
| TEST WATER SHUT-OFF | <input type="checkbox"/> | <input type="checkbox"/> |
| FRACTURE TREAT | <input type="checkbox"/> | <input type="checkbox"/> |
| SHOOT OR ACIDIZE | <input type="checkbox"/> | <input type="checkbox"/> |
| REPAIR WELL | <input type="checkbox"/> | <input type="checkbox"/> |
| PULL OR ALTER CASING | <input type="checkbox"/> | <input type="checkbox"/> |
| MULTIPLE COMPLETE | <input type="checkbox"/> | <input type="checkbox"/> |
| CHANGE ZONES | <input type="checkbox"/> | <input type="checkbox"/> |
| ABANDON* | <input type="checkbox"/> | <input type="checkbox"/> |
| (other) Spud date & surface csg./x/ | | |

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spuded @ 7:00 p.m. 9-2-84 MDT.
Drilled 12 1/4" Hole to 425'
Ran 10 jts. 8-5/8" 24# K-55 ST&C csg. w/float shoe,
Float collar, & 3 Centralizers set @ 425'.
Western cemented w/300 sx Class "C" + 1/4#/sk Cello-Seal
+ 2% CAC12 (1.32 ft. 3/sk, 14.8 ppg.). Plug down @ 9:30 A.M.
MDT 9-3-84. Bumped plug to 800# floats held.
Circ. 704 sk to surface. WOC 13 1/2 hrs. Tested BOPE to 1000#.
Held OK. DRLD. - Plug, cement & Shoe.
Drilling 7-7/8" Hole 9-3-84.

Subsurface Safety Valve: Manu. and Type ----- Set @ ----- Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED R. L. Hutchens TITLE Sr. Production Clerk DATE 9-5-84

ACCEPTED FOR RECORD (This space for Federal or State office use)

APPROVED BY [Signature] TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY

SEP 7 1984

Carleton

NEW MEXICO

*See Instructions on Reverse Side