

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR

Perry R. Bass

3. ADDRESS OF OPERATOR

P. O. Box 2760 Midland, TX 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FNL & 660' FWL Unit Letter E

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) Core # 1, & #2, 5 1/2 csg. (x)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled 7 7/8" hole to 3,835' 9-12-84. Logging, Core #1-3650'-3710' 60' Recovery 100%. Core #2-3710'-3770' 60' Recovery 100%. Ran 90 jts. 5 1/2" 14# K-55 ST&C Csg. w/float collar & float shoe & 5 centralizers. Set @ 3,835'.

Western cemented w/425 sx Class "H" + 8#/sk salt + 1/4#/sk Celloseal Mix (15.8 ppg, 1.18 yield). Plug down @ 9:15 A.M. MDST 9-13-84. Bumped plug to 1100 psi, Floats held, calculated TOC 2600'. Released Rig @3:00 p.m. 9-13-84. Final Report, wait on completion.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED R. C. Harkness TITLE Sr. Prod. Clerk DATE 9-17-84

ACCEPTED FOR RECORD (This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

SEP 21 1984

Car. C. C. C. NEW MEXICO

\*See Instructions on Reverse Side

clsf