

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	✓
FILE	✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	✓

<p>RECEIVED BY P. O. BOX 2088 SANTA FE, NEW MEXICO 87501</p> <p>JAN 15 1985</p> <p>O. C. D. ARTESIA, OFFICE</p>	<p>RECEIVED BY</p> <p>JAN 18 1985</p> <p>O. C. D. ARTESIA, OFFICE</p>
---	---

Form C-103  
Revised 10-1-78

3a. Indicate Type of Lease  
State ☐ Fee ☒

3. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator: Ray Westall ✓

Address of Operator: P.O. Box 4 Loco Hills, NM 88255

Location of Well: UNIT LETTER 1, 1980 FEET FROM THE South LINE AND 660 FEET FROM THE East LINE, SECTION 24 TOWNSHIP 22S RANGE 26E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name: Baseball Park

9. Well No.: 1

10. Field and Pool, or Wildcat: S. Carlsbad Delaware

15. Elevation (Show whether DF, RT, GR, etc.): 3169. GR

12. County: Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	
		OTHER Spud, 8 5/8" csg, T.D., 5 1/2" csg.	

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12-15-84 Spud 12 1/4" hole @ 5:00 P.M.

12-16-84 Ran 10 jts. 8 5/8" csg, J-55 24#, 421', set & cemented @ 418' w/250 sxs Class "C" 2% CaCl<sub>2</sub>. Circulated 25 sxs to pit. Plug down @ 10:00 A.M. WOC 18 hrs. Pressured up 1,000 PSI for 30 min. Held.

12-30-84 T.D. 4950'

12-31-84 Ran 118 jts. 5 1/2" J-55, 17# csg, 4974' set & cemented @ 4950' w/800 sxs Pacesetter Lite + 8# sk salt, tall in w/800 sxs Class "C" + .6% CF-1 + .2% AFS + 5# sk salt. Plug down @ 10:00 P.M. Circulated 50 sxs to pit. WOC 18 hr. press. test 1000 psi, 30 min, held.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ray Westall TITLE Operator DATE 1-14-85

APPROVED BY TITLE ORIGINAL SIGNED BY LARRY BROOKS DATE FEB 18 1984  
CONDITIONS OF APPROVAL, IF ANY: GEOLOGIST - NMOC