

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Exp. 3-5-85

| | | | | | |
|-------------------------------------|------------------|--------------------------------------|------------------------------------|---------------------|--------------------------|
| Operator <u>Monsanto Oil Co.</u> | | Lease <u>Burton Flat Deep Ut.</u> | | Well # <u>37</u> | |
| Location of Well | Unit <u>Q</u> | Section <u>2</u> | Township <u>21</u> | Range <u>27</u> | County <u>Soldado</u> |
| Drilling Contractor | <u>Unknown</u> | | Type of Equipment <u>Rotary</u> | | |

* Witness

APPROVED CASING PROGRAM

| Size of Hole | Size of Casing | Weight Per Foot | New or Used | Depth | Sacks Cement |
|---------------|--------------------|-----------------|-------------|--------------|--------------------|
| <u>17 1/2</u> | <u>13 3/8 H-40</u> | <u>48.0 #</u> | | <u>600+</u> | <u>500 Circ SX</u> |
| <u>11</u> | <u>8 5/8 J-55</u> | <u>24.0 #</u> | | <u>2500+</u> | <u>700 Circ</u> |
| <u>7 7/8</u> | <u>5 1/2 K-55</u> | <u>15.5 #</u> | | <u>5700+</u> | <u>750 SX</u> |

Casing Data:

Surface _____ joints of 8 7/8 inch 24 # Grade J-55

yes (Approved) (Rejected)

Inspected by BWW date _____

Cementing Program

Size of hole 12 1/4 Size of Casing 8 7/8 Sacks cement required 200

Type of Shoe used Tex-Pat Float collar used Insert Btm 3 jts welded yes

TD of hole 2553 Set 2553 Feet of 8 7/8 Inch 24 # Grade J-55

New-used csg. @ 2553 with 200 sacks neat cement around shoe

+ 200 sack Thick Set additives 1000 Pace Setter lite

Plug down @ 9:00 (AM) (PM) Date 11-9-84

Cement circulated yes No. of Sacks 100

Cemented by Western Witnessed by BWW

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____