Submit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISIOND
P.O. Box 2088

Santa Fe New Mexico 87504-2088

WELL API NO.

DISTRICT II Santa Fe, New Mexico 8 P.O. Drawer DD, Artesia, NM 88210	7504-2088 1 7 199 5. Indicate Type of Lease
DISTRICT III	STATE X FEE
1000 Rio Brazos Rd., Azzec, NM 87410	O. C. D. 6. State Oil & Gas Lease No. L-3568
SUNDRY NOTICES AND REPORTS ON WELL	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN O DIFFERENT RESERVOIR. USE "APPLICATION FOR PERI	
(FORM C-101) FOR SUCH PROPOSALS.)	No. 14-08-0001-12391
1. Type of Well: Off. GAS WELL OTHER	Burton Flat Deep Unit
2. Name of Operator BHP Petroleum (Americas) Inc.	8. Well No. 37
3. Address of Operator 5847 San Felipe Ste 3600 Houston TX 77057	9. Pool name or Wildcat N.W. Fenton-Delaware
4. Well Location Unit Letter Q 1980 Feet From The South	Line and 660 Feet From The East Line
	e 27-E NMPM Eddy County
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	
11. Check Appropriate Box to Indicate N	ature of Notice, Report, or Other Data
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON	REMEDIAL WORK ALTERING CASING
TEMPORARILY ABANDON CHANGE PLANS	COMMENCE DRILLING OPNS. DLUG AND ABANDONMENT X
PULL OR ALTER CASING	CASING TEST AND CEMENT JOB Post T0-2
OTHER:	OTHER:
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.	
10/7/91: LD rods & pump. NDWH, NUBOP. Release T.A.C. & POOH w/ 2-7/8" tbg. RUWL and set CIBP @ 2750'. RIH w/open-ended 2-7/8" tbg. Tagged CIBP @ 2750'.	
10/8/91: Circ hole w/9.5#/gal mud laden fluid. Spotted a 30 sx Class "H" plug from 2750' back up to 2500'F.S. Jet cut 5-1/2" csg @ 1079' F.S.	
10/9/91: LD 26 jts of 5-1/2" csg . RIH w/tbg down to 1137' and spotted a 25 sx plug (50' in/50' out of csg stub). Spotted a 35 sx plug @ 658'.	
10/10/91: RIH w/tbg and tagged solid at 1078'. NU to pump and spotted 30 sx cement at 14.5-15 ppg. P&L dn tbg to 655. Spotted 35 sx cmt 14.8-15.3 ppg. P&L dn tbg to 64'. Circ cmt to surf w/20 sx cmt at 14.5-14.8 ppg. Dug out cellar and cut off wellhead, cut anchors and installed P&A marker.	
I hereby certify that the information above to true and complete to the best of my knowledge and belief.	
SIGNATURE TIME	Drlg/Operations Engr. DATE 10/10/91
TYPE OR PRINT NAME Sam Brandon	(713) 780-5000 TELEPHONE NO.
(This space for State Use)	
APPROVED BY Mile Shelfelidel TITTE	E CH AND CAS INSPECTOR DATE MAY - 3 1993