

C/SF

UNITED STATES OIL CONS. COMMISSION
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
Artesia, NM 88210

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ well other2. NAME OF OPERATOR
Robert N. Enfield3. ADDRESS OF OPERATOR
P.O. Box 2431, Santa Fe, NM 87501

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE 200' FSL & 330' FEL of Sec. 18
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☐(other) SPUDDING - 13 3/8" CASING

SUBSEQUENT REPORT OF:

☐☐☐☐☐☐☐☐☒

RECEIVED BY

OCT 04 1984

O. C. D.

ARTESIA, OFFICE

5. LEASE

NM-0424859

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Bunel Federal9. WELL NO.
210. FIELD OR WILDCAT NAME
Indian Basin Upper Penn11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 18, T21S, R23E12. COUNTY OR PARISH
Eddy13. STATE
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
4075.5 GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 17-1/2" hole on 9/15/84 at 3:00 PM. Ran 13-3/8" 61#/ft., K-55, ST&C casing & cemented as follows on 9/16 & 17/84: Cemented w/100 sx Halliburton Lite Thick Set with 1/4# flocele/sx., (1.32 cu.ft./sk. yield, 14.8#/gallon weight). Followed w/275 sx Class "C" with 2% CACL2 (1.50 cu.ft./sx. yield, 14.1#/gallon weight). Displaced w/38-1/2 bbls fresh water. Plug down at 11:00 AM MDT. Maximum pressure 400 psig. Then waited 4-1/2 hrs. & tagged cement with 1" at 160'. Spotted 1" at 148' and set plugs as follows:

Plug No. 1: Pumped 35 sx, had 5' fill.

Plug No. 2: Pumped 35 sx, had no fill.

Plug No. 3: Pumped 50 sx, had 35' fill. Tagged cement at 109'

Plug No. 4: Pumped 50 sx, had 50' fill. Tagged cement at 59'

Plug No. 5: Pumped 50 sx, circulated 10 sx to surface

Job complete at 2:15 AM 9/18/84. Tested casing w/Hydrill to 1500 PSIG-OK Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert N. Enfield
Robert N. Enfield

TITLE Operator

DATE 9/27/84

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL

TITLE

DATE

OCT 3 1984

Carlsbad

NEW MEXICO

*See Instructions on Reverse Side