orm 9-331 Peter 1980 CONNIESION	Form Approved. Budget Bureau No. 42-R1424
	5. LEASI NM-0424859
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)	7. UNIT AGREEMENT NAME
	8, FARM OR LEASE NAME Bunnel Federa
1. oil gas well other	9 WELL NO. ARTESIA, OFFICE
2. NAME OF OPERATOR Tobert N. Enfield	10. FIELD OR WILDCAT NAME Indian Basin Upper Penn
3. ADDRESS OF OPERATOR P.O. BOX 2431, Santa Fe, NM 87501	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	Sec. 18, T21S, R23E
AT SURFACE200' FSL & 330' FEL of Sec. 18 AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE Eddy NM
AT TOTAL DEPTH: 6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 4075.5 GL
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:   rest water shut-off Image: Constraint of the second seco	(NOTE: Report results of multiple completion or zone
AULTIPLE COMPLETE	change on Form 9–330.)
other) INTER MEDIATE CASING X	- • • · · · · · · · · · · · · · · · · ·
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stat including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertinent	lirectionally drilled, give subsurface locations and
September 20, 1984: Drilled a 12-1/4" hole to 8-5/8" 24#/ft, J-55 ST&C casing and set at 162	a depth of 1622'. Ran 2' KB.
CEMENTING DETAIL:	
Cemented with 1000 gallons Flo-Check. 100 sac 1/4# flocele/sk., (1.51 cu.ft./sk., yield, 14. Halliburton Lite with 1/4# flocele/sk., 10# gi cu.ft./sk., yield, 12.1#/gallon weight). Foll with 1/4# flocele/sk., 2% CACL2, (1.32 cu.ft./ weight). Displaced with 101 barrels fresh wat maximum pressure 850 psi. Circulated 100 sack	1#/gallon weight). 515 sacks lsonite/sk., 2% CACL2, (l.84 owed with 100 sacks Class "C" sk., yield, 14.8#/gallon er. Plug down at 2:15 AM,
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct SIGNED TITLE DEPARTMENT OF TITLE DEPARTOR	DATE 10/3/84
(This space for Federal or State of	fice use)
APPROVED BY HUQ TITLE	DATE
CONDITIONS OF APPROVAL FORY: 1904	